



NUDECK

WOOD AND CONCRETE RESTORATIVE COATING



RENEW WOOD

TINTABLE COLORS

RENEW CONCRETE



Beige



Beechwood Gray



Black Canyon



Butternut



California Rustic



Cape Cod Gray



Cedarwood



Chocolate



Colonial Yellow



Deep Charcoal



Deep Desert Sand



Fawn



Hunter Green



Mahogany



Manor Brown



Navajo White



New Pilgrim Red



Parchment



Pilgrim Blue



Platinum



Prairie Gold



Sable



Salem Tan



Sage



Sandpiper



Sierra Redwood



Stonehedge



Winter White

NOTE: Color samples are subject to the effects of heat, light, age and other processes beyond our control and may vary slightly from the actual color. For accurate color match we recommend an initial brushout on the surface to be coated. Grit shown is representational of textured finish of product.

UGL®

THE MAKERS OF ZAR® AND DRYLOK®

NUDECK

WOOD AND CONCRETE RESTORATIVE COATING

APPLICATION GUIDE AND COLOR CARD

UGL® UNITED GILSONITE LABORATORIES

www.ugl.com

Order No. 15540 | LRS15

Scranton, PA | Jacksonville, IL | Jackson, MS | Dayton, NV

A 'NEW DECK' IN EVERY CAN



UGL® NuDECK® is a water-based paintable solution for damaged and aged wood and concrete surfaces. It creates a new, mildew-resistant, non-slip surface for wooden decks, docks, pool decks, concrete porches and walkways. **NuDECK** incorporates elastomeric technology to fill up to ¼ inch cracks and nail holes and locks down splinters on wood surfaces for a beautiful new finish.

NuDECK is for horizontal and vertical surfaces and can be coordinated with **ZAR®** Solid Color Deck and Siding Stain to compliment the color of surfaces such as siding, railings, posts and walls.

NuDECK will renew old and damaged concrete and wood surfaces with no special applicators, primers or topcoats. It will withstand the harsh natural elements and normal wear, while maintaining an aesthetically pleasing look and feel through many years of enjoyable use.

SURFACE PREP

- Surface area must be clean, dry and free of dirt, grease, oil, mill glaze, mildew and organic growth.
- Sand or scrape any loose wood fibers or flaking paint.
- Clean the surface with a mild household cleaner and water. Mildew and organic growth should be cleaned using: 1/3 cup heavy-duty laundry detergent to 1 quart household bleach to 3 quarts of warm water. Or use **ZAR®** Deck and Siding Cleaner for wood surfaces and **UGL DRYLOK®** Concrete Cleaner and Degreaser for concrete prior to painting. Apply cleaner with a scrub brush, rinse thoroughly and allow drying.

WARNING: If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WOOD PREP:

- Raised nail heads, deck screws or loose deck boards should be secured. Remove loose splinters and replace severely damaged or rotting boards. Sand glossy painted surfaces to improve adhesion.
- Synthetic or composite decking that is engineered with moisture repellants or sealers may prevent adhesion. Be sure to follow the specific manufacturer's recommendation for painting. Test a small area to determine adhesion.
- Cracks greater than 1/4 inch should be filled with an exterior paintable caulk.

CONCRETE PREP:

- Patch severe cracks (greater than ¼ inch), pockmarks and depressions in concrete with a suitable patching compound.
- Concrete should feel rough like sandpaper or have a broomed finish. For highly troweled or extremely smooth concrete, it will need to be etched with **DRYLOK Etch®** or muriatic acid. Remember to rinse thoroughly any etching solution from the surface and let the surface dry.
- New concrete surfaces should cure at least 30 days before applying **NuDECK**.
- Test concrete porosity by sprinkling a few drops of water onto the surface. If water beads or lays on the surface additional cleaning and etching is required.

APPLICATION:

Stir thoroughly before and during application. Apply when air and surface temperatures are between 50-90°F. Avoid applying in direct sunlight. Do not apply if rain is expected within 24 hours.



Using a good quality nylon bristle brush dab any damaged areas, holes, small cracks and chips with a brush coated with **NuDECK** to fill any voids then feather out the area. Cut-in the perimeter then apply the first coat using slight pressure to push the **NuDECK** into the surface using a 1/2 inch roller.



For a smoother look use a 3/8-1/4 inch nap roller. Cupped or warped boards will require rolling across the narrow width and then along the length to ensure uniform coverage.

Maintain a wet edge of **NuDECK** during application. Apply a minimum of 2 coats.

NOTE: When using two or more containers of the same color mix together to ensure color uniformity. Do not use on areas subjected to vehicular traffic.

COVERAGE:

Apply 2 coats at the rate of 100 sq. ft. per gallon.

CLEAN UP:

Clean all application tools with soap and water.