

ZAR® Deck & Siding Deck, Fence and Wood Brightener

MANUFACTURER

UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • FAX: 1-570-969-7634

www.ugl.com



PRODUCT DESCRIPTION

ZAR® Wood Brightener is a ready to use and an excellent choice for new and uncoated exterior wood decks, fences, wood siding and composite surfaces. This product will remove tannin stains from cedar or redwood as well as rust and nail head stains. Use this product to neutralize remaining stripper trapped in wood pores. The result will be a like-new appearance without the harmful effects on wood caused by bleach based cleaner/brighteners.

- Use after stripper or cleaner
- Ready to use, no mixing
- Brightens new or uncoated wood in preparation for new stain
- Restores wood's natural beauty

BASIC USES

Brightens new and uncoated exterior wood decks, fences, wood siding and composite surfaces.

LIMITATIONS

Exterior use only.

TECHNICAL DATA

COMPOSITION:

Oxalic acid solution

SHEEN:

N/A

% WEIGHT SOLIDS:

N/A

% VOLUME SOLIDS:

N/A

DENSITY (LBS./US GAL.):

8.79

VISCOSITY:

100-200 CPS

pH:

N/A

COLORS:

- N/A

ACTION TIME:

- 15 Minutes

CLEAN UP:

Soap and water

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

COVERAGE (SQ. FT./US 32 OZ.):

- Up to 250-300 sq. ft./gal.

Note: Actual coverage will vary depending upon application method, surface texture and porosity.

RECOMMENDED FILM THICKNESS/COAT:

N/A

FLASH POINT:

N/A

SHELF LIFE:

N/A

FREEZE/THAW:

Protect from freezing

CONTAINER SIZE:

One gallon (US) container.

VOC

<50%

TINTING

N/A

SURFACE PREPARATION

Wear protective eye goggles and waterproof gloves. Spray all vegetation thoroughly with water prior to and after application. Cover any areas you want to protect. Do not allow product to come in contact with fabric, furniture, metal or floor covering. DO NOT

mix with bleach or other chemicals. Always test a small hidden area.

APPLICATION

Product is ready to use. No mixing is necessary. Surface should be swept clean and dry. On vertical surfaces such as siding or fences apply product with a synthetic brush or deep nap roller working from bottom to top. On horizontal surfaces apply with a synthetic brush. Work from one end on 3-5 boards at a time. Allow product to sit on surface for 15-20 minutes keeping wet with additional product as needed. Scrub surface with a synthetic stiff bristle broom or brush. You can also use a power washer using 40 degree tip and on low (500-1000 psi) pressure. Make sure to thoroughly rinse the surface when completed. Allow wood to dry thoroughly before applying a water base finish and at least 24 hours before applying an oil base finish.

MAINTENANCE

N/A

CAUTION

OXALIC ACID EYE AND SKIN IRRITANT. Prevent eye and skin contact. During preparation and application wear safety goggles and rubber or PVC gloves. May be harmful if swallowed. May cause respiratory and throat irritation. Do not breathe spray mist, if applying with a sprayer wear a NIOSH-approved respirator. Use only with adequate ventilation.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.



ACTION TIME:
15 Minutes



CLEAN-UP:
Soap and Water



COVERAGE:
1 Application,
Reapply if Needed



SPREAD RATE:
250-300 Sq.
Ft./Gallon

KEEP OUT OF REACH OF CHILDREN
KEEP FROM FREEZING

FIRST AID

EYES: Flush immediately with large amounts of water for at least 15 minutes. SEEK MEDICAL ATTENTION.

SKIN: Wash affected area immediately with large amounts of water for at least 15 minutes. Remove contaminated clothing and launder before reuse. Seek medical attention if symptoms persist.

INGESTION: If swallowed. DO NOT induce vomiting. Immediately give 1 or 2 glasses of water or milk to dilute. GET MEDICAL ATTENTION IMMEDIATELY.

INHALATION: If difficulty in breathing is experienced, leave area for fresh air. GET MEDICAL ATTENTION IMMEDIATELY.

HANDLING AND STORAGE

Avoid extreme temperatures. Store in a cool, dry area. Close container after use. Do not mix with other household chemicals; generation of hazardous gases may occur.

DISPOSAL

Use up or give away excess product. Do not reuse empty container.

For additional health and safety information please refer to the "Safety Data Sheet".

WARRANTY

N/A



Deck & Siding Brightener
1 GAL. 4/Case40413

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.