

ZAR® Deck & Siding Deck, Fence and Wood Cleaner

MANUFACTURER

UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • FAX: 1-570-969-7634

www.ugl.com



PRODUCT DESCRIPTION

ZAR® Deck Cleaner is designed specifically to clean and brighten wood decks, fences, wood siding or composite surfaces for routine maintenance or prior to coating. It removes surface dirt and stains caused by mildew and algae to improve the adhesion of coatings. It brightens gray wood to like-new appearance. It penetrates deep into the wood surface and lifts out stains allowing dirt to be rinsed away.

- Use before applying stain or finishes
- Ready to use, no mixing
- Remove surface dirt and stains caused by mildew and algae
- Use for routine cleaning of composite decks

BASIC USES

ZAR® Deck Cleaner is designed specifically to clean and brighten wood decks, fences, wood siding or composite surfaces for routine maintenance or prior to coating.

LIMITATIONS

Exterior use only.

TECHNICAL DATA

COMPOSITION:

Sodium Metasilicate Solution

SHEEN:

N/A

% WEIGHT SOLIDS:

N/A

% VOLUME SOLIDS:

N/A

DENSITY (LBS./US GAL.):

8.56

VISCOSITY:

N/A

pH:

N/A

COLORS:

- N/A

ACTION TIME:

- 10 Minutes

CLEAN UP:

Soap and water

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

COVERAGE (SQ. FT./US 32 OZ.):

- Up to 250-300 sq. ft./gal.

Note: Actual coverage will vary depending upon application method, surface texture and porosity.

RECOMMENDED FILM THICKNESS/COAT:

N/A

FLASH POINT:

N/A

SHELF LIFE:

N/A

FREEZE/THAW:

Protect from freezing

CONTAINER SIZE:

One gallon (US) container.

VOC

<4%

TINTING

N/A

SURFACE PREPARATION

Wear protective eye goggles and waterproof gloves. Spray all vegetation thoroughly with

water prior to and after application. Cover any areas you want to protect. Do not allow product to come in contact with fabric,

furniture, metal or floor covering. DO NOT mix with bleach or other chemicals. Always test a small hidden area. May cause redwood to darken, new wood to discolor in spots and a blurred appearance on wood damaged by pressure washing.

APPLICATION

Sweep surface clean. Apply liberally to a dry surface at full strength with a roller or plastic garden sprayer and allow to stand for 10 minutes. Cleaning may occur without scrubbing but for quicker results scrub with a synthetic stiff bristle brush. You can use a hose or power washer using a 40 degree tip on low (500-1000psi). Rinse thoroughly with plenty of water. When cleaning vertical surfaces start at the bottom and work up. Allow surface to dry and repeat application if necessary.

Allow wood to dry thoroughly before applying a water base finish and at least 24 hours before applying an oil base finish.

MAINTENANCE

N/A

CAUTION

CONTAINS SODIUM METASILICATE AND SODIUM CARBONATE CORROSIVE: May be harmful or fatal if swallowed. EYE AND SKIN IRRITANT. MAY CAUSE BURNS WITH PROLONGED CONTACT. Prevent eye and skin contact. During preparation and application wear safety goggles and rubber or PVC gloves. May cause respiratory and throat irritation. Do not breathe spray mist, if applying with a sprayer wear a NIOSH-approved respirator. Use only with adequate ventilation.

WARNING: This product contains chemicals



ACTION TIME:
10 Minutes



CLEAN-UP:
Soap and Water



COVERAGE:
1 Application,
Reapply if Needed



SPREAD RATE:
250-300 Sq.
Ft./Gal.

known to the State of California to cause cancer and birth defects or other reproductive harm.

KEEP OUT OF REACH OF CHILDREN
KEEP FROM FREEZING

FIRST AID

EYES: Flush immediately with large amounts of water for at least 15 minutes. SEEK MEDICAL ATTENTION.

SKIN: Wash affected area immediately with large amounts of soap and water. Remove contaminated clothing and laundry before reuse. Seek medical attention if symptoms persist..

INGESTION: If swallowed. DO NOT induce vomiting. Immediately give 1 or 2 glasses of water or milk to dilute. GET MEDICAL ATTENTION IMMEDIATELY.

INHALATION: If difficulty in breathing is experienced, leave area for fresh air. GET MEDICAL ATTENTION IMMEDIATELY.

HANDLING AND STORAGE

Avoid extreme temperatures. Store in a cool, dry area. Close container after use. Do not mix with other household chemicals; generation of hazardous gases may occur.

DISPOSAL

Use up or give away excess product. Do not reuse empty container.

For additional health and safety information please refer to the "Safety Data Sheet".

WARRANTY

N/A



Deck & Siding Cleaner
1 GAL. 4/Case40213

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.