







---

<b>Inhalation</b>	Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Seek immediate medical attention/advice. Delayed pulmonary edema may occur.
<b>Ingestion</b>	Aspiration hazard if swallowed - can enter lungs and cause damage. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Remove all sources of ignition.

**Most important symptoms and effects, both acute and delayed**

<b>Most Important Symptoms and Effects</b>	Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.
--	--

**Indication of any immediate medical attention and special treatment needed**

<b>Notes to Physician</b>	May cause sensitization of susceptible persons. Treat symptomatically.
---------------------------	--

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray. Alcohol resistant foam.

### Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

### Specific Hazards Arising from the Chemical

Product is or contains a sensitizer. May cause sensitization by skin contact. Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

#### **Uniform Fire Code**

Combustible Liquid: II  
Sensitizer: Liquid

### Hazardous Combustion Products

Carbon oxides.

### Explosion Data

**Sensitivity to Mechanical Impact** No.

**Sensitivity to Static Discharge** Yes.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. See section 8 for more information. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

**Other Information** Refer to protective measures listed in Sections 7 and 8. Ventilate the area.

### Environmental Precautions

**Environmental Precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

### Methods and material for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

### Conditions for safe storage, including any incompatibilities

**Storage** Store locked up. Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Keep out of the reach of children. Store away from other materials. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

**Incompatible Products** None known based on information supplied.



**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Mineral Spirits (Rule 66) 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m <sup>3</sup>	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>
Third Party Formulation (TP # 1170003)	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m <sup>3</sup>	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>
Silica, amorphous, precipitated and gel 112926-00-8	-	(vacated) TWA: 6 mg/m <sup>3</sup>	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

**Appropriate engineering controls**

**Engineering Measures**

- Showers
- Eyewash stations
- Ventilation systems

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection**

Tight sealing safety goggles.

**Skin and Body Protection**

Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant apron. Impervious gloves. Antistatic boots.

**Respiratory Protection**

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Take off contaminated clothing and wash before reuse. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Physical and Chemical Properties**

**Physical State**  
**Appearance**  
**Color**

Liquid  
Amber  
No information available

**Odor**  
**Odor Threshold**

Aliphatic hydrocarbons  
No information available

**Property**  
**pH**

**Values**  
UNKNOWN

**Remarks** **Method**  
None known



<b>Melting / freezing point</b>	No data available	None known
<b>Boiling point / boiling range</b>	177 °C / 351 °F	None known
<b>Flash Point</b>	40 C / 104 F	None known
<b>Evaporation Rate</b>	No data available	None known
<b>Flammability (solid, gas)</b>	No data available	None known
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit</b>	No data available	
<b>Lower flammability limit</b>	No data available	
<b>Vapor pressure</b>	No data available	None known
<b>Vapor density</b>	No data available	None known
<b>Specific Gravity</b>	No data available	None known
<b>Water Solubility</b>	Insoluble	None known
<b>Solubility in other solvents</b>	No data available	None known
<b>Partition coefficient: n-octanol/water</b>	No data available	None known
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>	No data available	None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	No data available	None known
<b>Explosive properties</b>	No data available	
<b>Oxidizing Properties</b>	No data available	

**Other Information**

<b>Softening Point</b>	No data available
<b>VOC Content (%)</b>	No data available
<b>Particle Size</b>	No data available
<b>Particle Size Distribution</b>	

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available.

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Hazardous Polymerization**

Hazardous polymerization does not occur.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

None known based on information supplied.

**Hazardous Decomposition Products**

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**



**Product Information**

**Inhalation** Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract.

**Eye Contact** Specific test data for the substance or mixture is not available. May cause irritation.

**Skin Contact** Repeated exposure may cause skin dryness or cracking.

**Ingestion** Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

**Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketoxime 96-29-7	= 930 mg/kg ( Rat )	= 0.2 mg/kg ( Rabbit )	= 20 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Asthma-like and/ or skin allergy-like symptoms.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** May cause sensitization of susceptible persons. May cause sensitization by skin contact.

**Mutagenic Effects** There is no data available for this product. Contains a known or suspected mutagen.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Silica, amorphous, precipitated and gel 112926-00-8		Group 3		

*IARC (International Agency for Research on Cancer)  
Group 3 - Not Classifiable as to Carcinogenicity in Humans  
OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
X - Present*

**Reproductive Toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Chronic Toxicity** Contains a known or suspected mutagen. Possible risk of irreversible effects. Contains a known or suspected carcinogen. Aspiration may cause pulmonary edema and pneumonitis.

**Target Organ Effects** Skin. May affect the genetic material in germ cells (sperm and eggs). Respiratory system. Eyes. Gastrointestinal tract (GI). Central Nervous System (CNS). Kidney. Liver. Testes.

**Aspiration Hazard** No information available.



**Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document  
 Not applicable

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Methyl ethyl ketoxime 96-29-7	72h EC50: = 83 mg/L (Desmodesmus subspicatus)	96h LC50: 777 - 914 mg/L (Pimephales promelas) 96h LC50: 320 - 1000 mg/L (Leuciscus idus) 96h LC50: = 760 mg/L (Poecilia reticulata)	EC50 = 281 mg/L 17 h EC50 = 950 mg/L 5 min	48h EC50: = 750 mg/L

**Persistence and Degradability**

No information available.

**Bioaccumulation**

Chemical Name	Log Pow
Methyl ethyl ketoxime 96-29-7	0.65

**Other adverse effects**

No information available.

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

- Disposal methods** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
- Contaminated Packaging** Dispose of contents/containers in accordance with local regulations.
- US EPA Waste Number** D001

**California Hazardous Waste Codes 331**

This product contains one or more substances that are listed with the State of California as a hazardous waste.

**14. TRANSPORT INFORMATION**



**DOT** NOT REGULATED (IF SHIPPED IN NON BULK PACKAGING BY GROUND TRANSPORT)  
**Proper Shipping Name** NON-REGULATED  
**Hazard Class** N/A  
**Emergency Response Guide Number** 128

**TDG**  
**UN-No.** UN1263  
**Proper Shipping Name** PAINT  
**Hazard Class** 3  
**Packing Group** III  
**Description** UN1263, PAINT, 3, III

**MEX**  
**UN-No.** UN1263  
**Proper Shipping Name** PAINT  
**Hazard Class** 3  
**Packing Group** III  
**Description** UN1263 PAINT,3,III

**ICAO**  
**UN-No.** UN1263  
**Proper Shipping Name** PAINT  
**Hazard Class** 3  
**Packing Group** III  
**Description** UN1263,PAINT,3,PG III

**IATA**  
**UN-No.** UN1263  
**Proper Shipping Name** PAINT  
**Hazard Class** 3  
**Packing Group** III  
**Description** UN1263,PAINT,3,PG III

**IMDG/IMO**  
**UN-No.** UN1263  
**Proper Shipping Name** PAINT  
**Hazard Class** 3  
**Packing Group** III  
**EmS-No.** F-E, S-E  
**Description** UN1263, PAINT,3,PG III, FP 40C

**RID**  
**UN-No.** UN1263  
**Proper Shipping Name** PAINT  
**Hazard Class** 3  
**Packing Group** III  
**Classification code** F1  
**Description** UN1263 PAINT,3,III

**ADR**  
**UN-No.** UN1263  
**Proper Shipping Name** PAINT  
**Hazard Class** 3  
**Packing Group** III

<b>Classification code</b>	F1
<b>Description</b>	UN1263 PAINT,3,III

**ADN**

<b>UN-No.</b>	UN1263
<b>Proper Shipping Name</b>	PAINT
<b>Hazard Class</b>	3
<b>Packing Group</b>	III
<b>Classification code</b>	F1
<b>Special Provisions</b>	163, 640H, 650
<b>Description</b>	UN1263 PAINT,3,III
<b>Hazard Labels</b>	3
<b>Limited Quantity</b>	LQ7
<b>Ventilation</b>	VE01

## 15. REGULATORY INFORMATION

**International Inventories**

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**SARA 311/312 Hazard Categories**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	Yes
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

**US State Regulations****California Proposition 65**

This product does not contain any Proposition 65 chemicals.

**U.S. State Right-to-Know Regulations**

.



Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Mineral Spirits (Rule 66) 8052-41-3	X	X	X		
Third Party Formulation (TP # 1170003)	X	X	X		
Silica, amorphous, precipitated and gel 112926-00-8	X	X	X		
Hexanoic acid, 2-ethyl-, cobalt(2+) salt 136-52-7			X	X	X

**International Regulations**

**Mexico**

**National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Mineral Spirits (Rule 66) 8052-41-3 ( 30 - 60 )		Mexico: TWA 100 ppm Mexico: TWA 523 mg/m <sup>3</sup> Mexico: STEL 200 ppm Mexico: STEL 1050 mg/m <sup>3</sup>
Third Party Formulation (TP # 1170003) ( 10 - 30 )		Mexico: TWA 100 ppm Mexico: TWA 523 mg/m <sup>3</sup> Mexico: STEL 200 ppm Mexico: STEL 1050 mg/m <sup>3</sup>
Silica, amorphous, precipitated and gel 112926-00-8 ( 1 - 5 )		Mexico: TWA 10 mg/m <sup>3</sup>

Mexico - Occupational Exposure Limits - Carcinogens

**Canada**

**WHMIS Hazard Class**

- B3 - Combustible liquid
- D2A - Very toxic materials
- D2B - Toxic materials



**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health Hazards</b> 2	<b>Flammability</b> 2	<b>Instability</b> 0	<b>Physical and Chemical Hazards</b> -
<b>HMIS</b>	<b>Health Hazards</b> 2 *	<b>Flammability</b> 2	<b>Physical Hazard</b> 0	<b>Personal Protection</b> X

**Chronic Hazard Star Legend** \* = Chronic Health Hazard

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Revision Date** 09-Mar-2015

**Revision Note** No information available



**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**