

ZAR® Trowelable Wood Patch

MANUFACTURER

UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • FAX: 1-570-969-7634

www.ugl.com



PRODUCT DESCRIPTION

ZAR Trowelable Wood Patch is a low odor, ready-to-use, full trowel latex patching compound for interior use only. Trowelable Wood Patch contains treated pulverized wood to fill nail holes, repair cracks, gouges, chips, etc., in all types of wood. Special property allows ZAR Wood Patch to accept stain more uniformly than other wood fillers.

ZAR Trowelable Wood Patch may be nailed, sawed, sanded, or drilled. ZAR Wood Patch will take paint, varnish, shellac, polyurethanes and stains. When a patched area requires stain, ZAR Wood Patch greatly diminishes the lighter area of "halo" effect surrounding the patch normally present with other wood fillers. ZAR Wood Patch is non-flammable.

- Full trowel latex patching compound for floors
- Fills cracks, holes and gouges
- Accepts stain uniformly
- Greatly diminishes the lighter area or "halo" effect surrounding the patch when patch requires a wood stain
- May be sanded, nailed, sawed, drilled, painted, varnished, shellacked, polyurethaned or stained
- Water mixable
- Non-flammable, low odor

BASIC USES

ZAR Trowelable Wood Patch's creamy easy-to-sand formula is ideal for floor finishing. It fills open-grain and nail holes and repairs cracks and gouges on wood surfaces.

LIMITATIONS

Do not use a metal trowel or scraper. Do not use on exterior surfaces. Do not bleach.

TECHNICAL DATA

COMPOSITION:

Latex

SHEEN:

N/A

% WEIGHT SOLIDS:

74.5 ± 0.5%

% VOLUME SOLIDS:

55.3 ± 0.5%

DENSITY (LBS./US GAL.):

14.5 ± 0.3

VISCOSITY:

N/A

pH:

N/A

COLORS:

- 3 ready mixed colors

SET TIME:

- For latex stain or paint: 1 1/2 - 2 hours
 - For oil base stain, paint, varnish, shellac or polyurethane: overnight
- Note:** Maximum cure and dry time will be prolonged when slightly humid and damp, cool conditions prevail.

CLEAN UP:

Damp cloth before material dries.
Close container after each use.
Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

COVERAGE (SQ. FT./US GAL.):

- Up to 2600 sq. ft./gal.

Note: Actual coverage will vary depending upon application method, surface texture and porosity.

RECOMMENDED FILM THICKNESS/COAT:

N/A

FLASH POINT:

N/A

SHELF LIFE:

Unopened, 3 years

FREEZE/THAW:

Protect from freezing

CONTAINER SIZES:

Red Oak and White Oak: One gallon (US) containers and Three and a half gallon (US) containers. Maple/Ash/Pine is available in Three and a half gallon (US) containers

VOC

N/A

TINTING

N/A

SURFACE PREPARATION

Remove all dirt, grease, oil and loose particles from the patch area. Dampen surfaces to be patched with water. Do not use when material and/or air temperature is below 50°F.

WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.



SET TIME:

1 1/2 - 2 hours



CLEAN-UP:

Cloth Dampened with Water



COVERAGE:

Varies on Application



SPREAD RATE:

2600 Sq. Ft./Gallon

APPLICATION

Pour ZAR Trowelable Wood Patch on the floor surface. Using a non-metallic, smooth edge finishing trowel spread the wood patch across the entire surface. Be sure to press ZAR Trowelable Wood Patch into the surface to fill all cracks. May be sanded after one hour. Deep areas should be filled in layers allowing each layer to dry between applications. Sand after last layer has completely dried. Final sanding should remove all ZAR Trowelable Wood Patch from the surface of the wood leaving the patch only in the surface cracks and nail holes.

Allow overnight drying of patch before applying an oil base stain - 1½ to 2 hours before applying latex paint.

CAUTION

Avoid breathing sanding dust.

KEEP OUT OF REACH OF CHILDREN
KEEP FROM FREEZING
CLOSE CONTAINER AFTER EACH USE

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

FIRST AID

EYES: Immediately flush eye thoroughly with water for at least 15 minutes. Consult a physician if irritation persists.

SKIN: Wash affected area with soap and water. Consult a physician if irritation is present.

INGESTION: Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth. Place individual on the left side with head down. Contact a physician, medical facility or poison control center for advice about whether to induce vomiting.

INHALATION: Remove to fresh air.

For additional health and safety information please refer to the "Safety Data Sheet".



WARRANTY

N/A

SPECIFICATION

N/A



				
Trowelable Wood Patch	Red Oak	White Oak	Maple/Ash/Pine	
1 GAL. 2/Case	31113	31213	n/a	
3.5 GAL. 1/Case	31160	31260	31360	

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.