



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ZAR® Vintage Modern Stain

Version number: REV 1.0

Date of compilation: 2020-12-08

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name

**ZAR® Vintage Modern Stain**

Alternative number(s)

12906; UFI: KR99-UQ50-9302-T0PN  
12911; UFI: APPA-WQ8G-E30G-JQ1W  
12912; UFI: H8YA-HQ96-130Y-QUAC  
12913; UFI: CU7C-4Q9V-P30F-VYKT

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

General use

#### 1.3 Details of the supplier of the safety data sheet

Sika Corporation

1396 Jefferson Avenue  
Dunmore PA 18509  
United States

Telephone: +1 (570) 344-1202

Telefax: (570) 969-7634

e-mail:

[retailorders@us.sika.com](mailto:retailorders@us.sika.com)

Website: <http://www.zar.com/>

e-mail (competent person)

[crossley.robin@us.sika.com](mailto:crossley.robin@us.sika.com)

#### 1.4 Emergency telephone number

Emergency information service

1-800-424-9300 Chemtrec (NORTH AMERICA)  
This number is only available during the following office hours: Mon-Fri 08:00 AM - 05:00 PM

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

| Section | Hazard class            | Category | Hazard class and category | Hazard statement |
|---------|-------------------------|----------|---------------------------|------------------|
| A.11    | acute toxicity (inhal.) | 4        | Acute Tox. 4              | H332             |
| A.4S    | skin sensitization      | 1        | Skin Sens. 1              | H317             |
| A.6     | carcinogenicity         | 2        | Carc. 2                   | H351             |
| A.7     | reproductive toxicity   | 2        | Repr. 2                   | H361d            |
| A.10    | aspiration hazard       | 1        | Asp. Tox. 1               | H304             |
| B.6     | flammable liquid        | 3        | Flam. Liq. 3              | H226             |

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

#### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word

danger

## ZAR® Vintage Modern Stain

Version number: REV 1.0

Date of compilation: 2020-12-08

### - Pictograms

GHS02, GHS07, GHS08



### - Hazard statements

|       |   |
|-------|---|
| H226  | Flammable liquid and vapor.                   |
| H304  | May be fatal if swallowed and enters airways. |
| H317  | May cause an allergic skin reaction.          |
| H332  | Harmful if inhaled.                           |
| H351  | Suspected of causing cancer.                  |
| H361d | Suspected of damaging the unborn child.       |

### - Precautionary statements

|                |   |
|----------------|---|
| P201           | Obtain special instructions before use.   |
| P210           | Keep away from heat/sparks/open flames/hot surfaces. No smoking.                                    |
| P233           | Keep container tightly closed.  |
| P240           | Ground/bond container and receiving equipment.  |
| P241           | Use explosion-proof electrical/ventilating/lighting equipment.                                      |
| P242           | Use only non-sparking tools.  |
| P243           | Take precautionary measures against static discharge.   |
| P261           | Avoid breathing dust/fume/gas/mist/vapors/spray.  |
| P271           | Use only outdoors or in a well-ventilated area.   |
| P272           | Contaminated work clothing must not be allowed out of the workplace.                                |
| P280           | Wear protective gloves/eye protection/face protection.  |
| P301+P310      | If swallowed: Immediately call a poison center/doctor.  |
| P302+P352      | If on skin: Wash with plenty of water.  |
| P303+P361+P353 | If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304+P340      | If inhaled: Remove person to fresh air and keep comfortable for breathing.                          |
| P312           | Call a poison center/doctor if you feel unwell.   |
| P321           | Specific treatment (see on this label).   |
| P331           | Do NOT induce vomiting.   |
| P363           | Wash contaminated clothing before reuse.  |
| P370+P378      | In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.                     |
| P403+P235      | Store in a well-ventilated place. Keep cool.  |
| P405           | Store locked up.  |
| P501           | Dispose of contents/container to industrial combustion plant.                                       |

### - Hazardous ingredients for labelling

Talc ( $\text{Mg}_3\text{H}_2(\text{SiO}_3)_4$ ), Distillates (petroleum), hydrotreated light, ethyl methyl ketoxime, 2-ethylhexanoic acid

## 2.3 Other hazards

### Hazards not otherwise classified

Contains ethyl methyl ketoxime. May produce an allergic reaction.  
May be harmful in contact with skin (GHS category 5: acutely toxic - dermal).  
Toxic to aquatic life with long lasting effects (GHS category 2: aquatic toxicity - acute and/or chronic).

### Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ZAR® Vintage Modern Stain

Version number: REV 1.0

Date of compilation: 2020-12-08

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Not relevant (mixture)

#### 3.2 Mixtures

Description of the mixture

| Name of substance   | Identifier           | Wt%       | Classification acc. to GHS  |
|---|----------------------|-----------|---|
| Distillates (petroleum), hydro-treated light                            | CAS No<br>64742-47-8 | 25 – < 50 | Acute Tox. 3 / H331<br>Asp. Tox. 1 / H304<br>Flam. Liq. 3 / H226  |
| Kerosene  | CAS No<br>8008-20-6  | 1 – < 5   | Acute Tox. 3 / H331<br>Skin Irrit. 2 / H315<br>STOT SE 3 / H336<br>Asp. Tox. 1 / H304<br>Flam. Liq. 3 / H226                    |
| ethyl methyl ketoxime   | CAS No<br>96-29-7    | < 1       | Acute Tox. 4 / H312<br>Acute Tox. 3 / H331<br>Eye Dam. 1 / H318<br>Skin Sens. 1 / H317<br>Carc. 2 / H351<br>Flam. Liq. 4 / H227 |
| Naphtha (petroleum), hydro-treated heavy                                | CAS No<br>64742-48-9 | < 1       | Acute Tox. 3 / H331<br>STOT SE 3 / H336<br>Asp. Tox. 1 / H304<br>Flam. Liq. 3 / H226  |
| Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) | CAS No<br>14807-96-6 | < 1       | Acute Tox. 4 / H332<br>Carc. 2 / H351   |
| 2-ethylhexanoic acid  | CAS No<br>149-57-5   | < 1       | Repr. 2 / H361d   |

For full text of abbreviations: see SECTION 16.

### SECTION 4: First-aid measures

#### 4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ZAR® Vintage Modern Stain

Version number: REV 1.0

Date of compilation: 2020-12-08

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media

Water jet

### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO<sub>x</sub>), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ZAR® Vintage Modern Stain

Version number: REV 1.0

Date of compilation: 2020-12-08

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

##### Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

##### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedings.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

#### 7.3 Specific end use(s)

See section 16 for a general overview.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

| Occupational exposure limit values (Workplace Exposure Limits) |               |            |            |           |             |            |              |                 |                   |                      |                   |
|--|---------------|------------|------------|-----------|-------------|------------|--------------|-----------------|-------------------|----------------------|-------------------|
| Country  | Name of agent | CAS No     | Identifier | TWA [ppm] | TWA [mg/m³] | STEL [ppm] | STEL [mg/m³] | Ceiling-C [ppm] | Ceiling-C [mg/m³] | Notation             | Source            |
| US   | talc          | 14807-96-6 | PEL (CA)   | 1         |             |            |              |                 |                   | +asb, fib/cm³        | Cal/ OSHA PEL     |
| US   | talc          | 14807-96-6 | TLV®       |           | 0.1         |            |              |                 |                   | fib/cm³, +asb, CA-10 | ACGIH® 2019       |
| US   | talc          | 14807-96-6 | PEL        |           | 0.1         |            | 1 (30 min)   |                 |                   | no_asb, fib/ml       | 29 CFR 1910.10 00 |



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ZAR® Vintage Modern Stain

Version number: REV 1.0

Date of compilation: 2020-12-08

| Occupational exposure limit values (Workplace Exposure Limits) |  |            |            |           |             |            |              |                 |                   |                            |                  |
|--|--|------------|------------|-----------|-------------|------------|--------------|-----------------|-------------------|----------------------------|------------------|
| Country  | Name of agent                                    | CAS No     | Identifier | TWA [ppm] | TWA [mg/m³] | STEL [ppm] | STEL [mg/m³] | Ceiling-C [ppm] | Ceiling-C [mg/m³] | Notation                   | Source           |
| US   | talc   | 14807-96-6 | PEL (CA)   |           | 2           |            |              |                 |                   | no_asb, r, less1silica     | Cal/ OSHA PEL    |
| US   | talc   | 14807-96-6 | PEL        | 706       |             |            |              |                 |                   | partml, noAsb, less1Sil, r | 29 CFR 1910.1000 |
| US   | talc   | 14807-96-6 | REL        |           | 2 (10 h)    |            |              |                 |                   | r, less1silica, no_asb     | NIOSH REL        |
| US   | talc   | 14807-96-6 | TLV®       |           | 2           |            |              |                 |                   | r, noAsb, less1Sil         | ACGIH® 2019      |
| US   | 2-ethylhexanoic acid                             | 149-57-5   | TLV®       |           | 5           |            |              |                 |                   | iv                         | ACGIH® 2019      |
| US   | petroleum distillates (naphtha) (rubber solvent) | 64742-48-9 | PEL        | 500       | 2,000       |            |              |                 |                   |                            | 29 CFR 1910.1000 |
| US   | Kerosine (petroleum)                             | 8008-20-6  | REL        |           | 100 (10 h)  |            |              |                 |                   |                            | NIOSH REL        |
| US   | Kerosine (petroleum) (jet fuels, JP 5)           | 8008-20-6  | TLV®       |           | 200         |            |              |                 |                   | vap, HyCarb                | ACGIH® 2019      |

### Notation

|                |  |
|----------------|--|
| +asb           | containing asbestos fibers   |
| CA-10          | Respirable fibers: length > 5µm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450 times magnification (4-mm objective), using phase-contrast illumination. |
| Ceiling-C      | ceiling value is a limit value above which exposure should not occur   |
| fib/cm³        | fibers/cm³   |
| fib/ml         | fibers/ml  |
| HyCarb         | calculated as hydrocarbons   |
| iv             | inhalable fraction and vapor   |
| less1silica    | with less than 1 % free crystalline silica   |
| no_asb         | containing no asbestos fibers  |
| noAsb_less1Sil | contains no asbestos and less than 1% free crystalline silica  |
| partml         | particles/ml   |
| r              | respirable fraction  |
| STEL           | short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)                               |
| TWA            | time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours  |
|                | time-weighted average (unless otherwise specified)   |
| vap            | as vapors  |

## 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ZAR® Vintage Modern Stain

Version number: REV 1.0

Date of compilation: 2020-12-08

### Skin protection

#### - Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

|                |                |
|----------------|----------------|
| Physical state | liquid         |
| Color          | various        |
| Odor           | characteristic |

#### Other safety parameters

|   |                                   |
|---|-----------------------------------|
| pH (value)                              | not determined                    |
| Melting point/freezing point            | not determined                    |
| Initial boiling point and boiling range | ≥146 °C at 101.3 kPa              |
| Flash point                             | 29 °C at 101.3 kPa                |
| Evaporation rate                        | not determined                    |
| Flammability (solid, gas)               | not relevant, (fluid)             |
| Explosive limits                        | not determined                    |
| Vapor pressure                          | ≤3.7 kPa at 37.8 °C               |
| Density                                 | 0.934 g/cm <sup>3</sup> at 20 °C  |
| Vapor density                           | this information is not available |
| Solubility(ies)                         | not determined                    |

#### Partition coefficient

|                             |                                   |
|-----------------------------|-----------------------------------|
| - n-octanol/water (log KOW) | this information is not available |
|-----------------------------|-----------------------------------|



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ZAR® Vintage Modern Stain

Version number: REV 1.0

Date of compilation: 2020-12-08

|                           |  |
|---------------------------|--|
| Auto-ignition temperature | 220 °C (auto-ignition temperature (liquids and gases)) |
| Viscosity                 | not determined   |
| Explosive properties      | none   |
| Oxidizing properties      | none   |

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### 10.5 Incompatible materials

Oxidizers

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**

Acute toxicity

Harmful if inhaled.

GHS of the United Nations, annex 4: May be harmful in contact with skin.

- Acute toxicity estimate (ATE)

Inhalation: vapor 10.7 mg/l/4h





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ZAR® Vintage Modern Stain

Version number: REV 1.0

Date of compilation: 2020-12-08

| Acute toxicity estimate (ATE) of components of the mixture              |            |                       |              |
|---|------------|-----------------------|--------------|
| Name of substance   | CAS No     | Exposure route        | ATE          |
| Distillates (petroleum), hydrotreated light                             | 64742-47-8 | inhalation: vapor     | 5.28 mg/l/4h |
| Kerosene  | 8008-20-6  | inhalation: vapor     | 5.28 mg/l/4h |
| Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) | 14807-96-6 | inhalation: dust/mist | 2.1 mg/l/4h  |
| Naphtha (petroleum), hydrotreated heavy                                 | 64742-48-9 | inhalation: vapor     | 9.3 mg/l/4h  |
| ethyl methyl ketoxime   | 96-29-7    | dermal                | 1,000 mg/kg  |
| ethyl methyl ketoxime   | 96-29-7    | inhalation: vapor     | 4.83 mg/l/4h |

### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

### Respiratory or skin sensitization

May cause an allergic skin reaction.

### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

Suspected of causing cancer.

| IARC Monographs on the Evaluation of Carcinogenic Risks to Humans       |            |                |        |
|---|------------|----------------|--------|
| Name of substance   | CAS No     | Classification | Number |
| Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) | 14807-96-6 | 3              |        |
| Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) | 14807-96-6 | 2B             |        |

### Legend

2B Possibly carcinogenic to humans  
3 Not classifiable as to carcinogenicity in humans

### Reproductive toxicity

Suspected of damaging the unborn child.

### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### Aspiration hazard

May be fatal if swallowed and enters airways.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ZAR® Vintage Modern Stain

Version number: REV 1.0

Date of compilation: 2020-12-08

### SECTION 12: Ecological information

#### 12.1 Toxicity

Toxic to aquatic life with long lasting effects.

| Aquatic toxicity (acute) of components of the mixture                   |            |          |             |                       |               |
|---|------------|----------|-------------|-----------------------|---------------|
| Name of substance   | CAS No     | Endpoint | Value       | Species               | Exposure time |
| Distillates (petroleum), hydrotreated light                             | 64742-47-8 | LL50     | 5 mg/l      | fish                  | 96 h          |
| Distillates (petroleum), hydrotreated light                             | 64742-47-8 | EL50     | 1.4 mg/l    | aquatic invertebrates | 48 h          |
| Kerosene  | 8008-20-6  | LL50     | 5 mg/l      | fish                  | 96 h          |
| Kerosene  | 8008-20-6  | EL50     | 1.4 mg/l    | aquatic invertebrates | 48 h          |
| Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) | 14807-96-6 | LC50     | 89,581 mg/l | fish                  | 96 h          |
| Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) | 14807-96-6 | EC50     | 7,203 mg/l  | algae                 | 96 h          |
| Naphtha (petroleum), hydrotreated heavy                                 | 64742-48-9 | LL50     | >1,000 mg/l | fish                  | 24 h          |
| Naphtha (petroleum), hydrotreated heavy                                 | 64742-48-9 | EL50     | >1,000 mg/l | aquatic invertebrates | 24 h          |
| ethyl methyl ketoxime   | 96-29-7    | LC50     | >100 mg/l   | fish                  | 96 h          |
| ethyl methyl ketoxime   | 96-29-7    | EC50     | 201 mg/l    | aquatic invertebrates | 48 h          |
| ethyl methyl ketoxime   | 96-29-7    | ErC50    | 11.8 mg/l   | algae                 | 72 h          |
| 2-ethylhexanoic acid  | 149-57-5   | LC50     | >100 mg/l   | fish                  | 96 h          |
| 2-ethylhexanoic acid  | 149-57-5   | ErC50    | 49.3 mg/l   | algae                 | 72 h          |

| Aquatic toxicity (chronic) of components of the mixture |            |          |            |                       |               |
|---|------------|----------|------------|-----------------------|---------------|
| Name of substance                                       | CAS No     | Endpoint | Value      | Species               | Exposure time |
| Distillates (petroleum), hydrotreated light             | 64742-47-8 | EL50     | 0.89 mg/l  | aquatic invertebrates | 21 d          |
| Kerosene  | 8008-20-6  | EL50     | 0.89 mg/l  | aquatic invertebrates | 21 d          |
| Naphtha (petroleum), hydrotreated heavy                 | 64742-48-9 | EL50     | 10 mg/l    | fish                  | 21 d          |
| Naphtha (petroleum), hydrotreated heavy                 | 64742-48-9 | EC50     | 15.41 mg/l | microorganisms        | 40 h          |
| ethyl methyl ketoxime                                   | 96-29-7    | EC50     | ≥100 mg/l  | aquatic invertebrates | 21 d          |
| 2-ethylhexanoic acid                                    | 149-57-5   | EC50     | 75 mg/l    | aquatic invertebrates | 21 d          |

#### 12.2 Persistence and degradability

Data are not available.

#### 12.3 Bioaccumulative potential

Data are not available.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ZAR® Vintage Modern Stain

Version number: REV 1.0

Date of compilation: 2020-12-08

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Other adverse effects

Endocrine disrupting potential

None of the ingredients are listed.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## SECTION 14: Transport information

|      |  |   |
|------|--|---|
| 14.1 | UN number  | 3295  |
| 14.2 | UN proper shipping name  | Hydrocarbons, liquid, n.o.s.                |
| 14.3 | Transport hazard class(es)   |   |
|      | Class  | 3 (flammable liquids)                       |
| 14.4 | Packing group  | III (substance presenting low danger)       |
| 14.5 | Environmental hazards  | hazardous to the aquatic environment        |
|      | Environmentally hazardous substance (aquatic environment)          | Distillates (petroleum), hydrotreated light |
| 14.6 | Special precautions for user                                       |   |
|      | There is no additional information.                                |   |
| 14.7 | Transport in bulk according to Annex II of MARPOL and the IBC Code |   |
|      | The cargo is not intended to be carried in bulk.                   |   |

### Information for each of the UN Model Regulations

# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ZAR® Vintage Modern Stain

Version number: REV 1.0

Date of compilation: 2020-12-08

### Transport of dangerous goods by road or rail (49 CFR US DOT)

|  |   |
|--|---|
| Index number                               | 3295  |
| Proper shipping name                       | Hydrocarbons, liquid, n.o.s.  |
| - Particulars in the shipper's declaration | UN3295, Hydrocarbons, liquid, n.o.s., 3, III, environmentally hazardous |
| - Reportable quantity (RQ)                 | 5,070,994 lbs (2,302,231 kg) (naphthalene) (benzene)                    |
| Class                                      | 3   |
| Packing group                              | III   |
| Danger label(s)                            | 3, fish and tree  |



|                         |  |
|-------------------------|--|
| Environmental hazards   | yes (hazardous to the aquatic environment) |
| Special provisions (SP) | 144, B1, IB3, T4, TP1, TP29                |
| ERG No                  | 128  |

### International Maritime Dangerous Goods Code (IMDG)

|                      |  |
|----------------------|--|
| UN number            | 3295                                       |
| Proper shipping name | HYDROCARBONS, LIQUID, N.O.S.               |
| Class                | 3  |
| Marine pollutant     | yes (hazardous to the aquatic environment) |
| Packing group        | III  |
| Danger label(s)      | 3, fish and tree                           |



|                          |          |
|--------------------------|----------|
| Special provisions (SP)  | 223      |
| Excepted quantities (EQ) | E1       |
| Limited quantities (LQ)  | 5 L      |
| EmS                      | F-E, S-D |
| Stowage category         | A        |

### International Civil Aviation Organization (ICAO-IATA/DGR)

|                       |  |
|-----------------------|--|
| UN number             | 3295                                       |
| Proper shipping name  | Hydrocarbons, liquid, n.o.s.               |
| Class                 | 3  |
| Environmental hazards | yes (hazardous to the aquatic environment) |
| Packing group         | III  |
| Danger label(s)       | 3  |



|                          |      |
|--------------------------|------|
| Special provisions (SP)  | A3   |
| Excepted quantities (EQ) | E1   |
| Limited quantities (LQ)  | 10 L |



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ZAR® Vintage Modern Stain

Version number: REV 1.0

Date of compilation: 2020-12-08

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations specific for the product in question

##### National regulations (United States)

##### Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

| Name of substance                       | CAS No     | Functionality | Authoritative Lists                        |
|---|------------|---------------|--|
| Kerosene                                | 8008-20-6  |               | ATSDR Neurotoxicants<br>CWA 303(d)         |
| Naphtha (petroleum), hydrotreated heavy | 64742-48-9 |               | Canada PBITs<br>EC Annex VI CMRs - Cat. 1B |

- Hazardous Substances List (MN-ERTK)

| Name of substance   | CAS No     | References | Remarks |
|---|------------|------------|---------|
| Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) | 14807-96-6 | A, R, *    | fiber   |

##### Legend

- \* Substances which are regulated by OSHA as carcinogens; have been categorized by the ACGIH as either "human carcinogens" or "suspect of carcinogenic potential for man"; have been evaluated by the International Agency for Research on Cancer (IARC) and found to be carcinogens or potential carcinogens; or have been listed as a carcinogen or potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP).
- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- R International Agency for Research on Cancer (IARC) Monographs on the Evaluation of the Carcinogenic Risks to Humans; Overall Evaluations of Carcinogenicity: An Updating of IARC Monographs Volumes 1 to 42, Supplement 7 (1987). Available from: WHO Publications Centre USA

- Hazardous Substance List (NJ-RTK)

| Name of substance   | CAS No     | Remarks                       | Classifications |
|---|------------|-------------------------------|-----------------|
| Kerosene  | 8008-20-6  |                               | F2              |
| Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) | 14807-96-6 | containing no asbestos fibers |                 |
| Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) | 14807-96-6 | containing asbestos fibers    | CA              |
| 2-ethylhexanoic acid  | 149-57-5   |                               |                 |

##### Legend

- CA Carcinogenic
- F2 Flammable - Second Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

| Name acc. to inventory | CAS No    | Classification |
|------------------------|-----------|----------------|
| KEROSINE (PETROLEUM)   | 8008-20-6 |                |

- Hazardous Substance List (RI-RTK)

| Name of substance   | CAS No     | References |
|---|------------|------------|
| Kerosene  | 8008-20-6  | F          |
| Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) | 14807-96-6 | T          |

##### Legend

- F Flammability (NFPA®)
- T Toxicity (ACGIH®)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ZAR® Vintage Modern Stain

Version number: REV 1.0

Date of compilation: 2020-12-08

### California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

| Proposition 65 List of chemicals   |            |                                    |                      |
|------------------------------------|------------|------------------------------------|----------------------|
| Name acc. to inventory             | CAS No     | Remarks                            | Type of the toxicity |
| Talc containing asbestiform fibers | 14807-96-6 | Talc containing asbestiform fibers | cancer               |

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

| Category            | Rating | Description  |
|---------------------|--------|--|
| Chronic             | *      | chronic (long-term) health effects may result from repeated overexposure   |
| Health              | 2      | temporary or minor injury may occur  |
| Flammability        | 3      | material that can be ignited under almost all ambient temperature conditions   |
| Physical hazard     | 0      | material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive |
| Personal protection | -      |  |

#### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

| Category       | Degree of hazard | Description  |
|----------------|------------------|--|
| Flammability   | 3                | material that can be ignited under almost all ambient temperature conditions                     |
| Health         | 2                | material that, under emergency conditions, can cause temporary incapacitation or residual injury |
| Instability    | 0                | material that is normally stable, even under fire conditions                                     |
| Special hazard |                  |  |

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information, including date of preparation or last revision

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ZAR® Vintage Modern Stain

Version number: REV 1.0

Date of compilation: 2020-12-08

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

| Code  | Text  |
|-------|---|
| H226  | Flammable liquid and vapor.                   |
| H227  | Combustible liquid.                           |
| H304  | May be fatal if swallowed and enters airways. |
| H312  | Harmful in contact with skin.                 |
| H315  | Causes skin irritation.                       |
| H317  | May cause an allergic skin reaction.          |
| H318  | Causes serious eye damage.                    |
| H331  | Toxic if inhaled.                             |
| H332  | Harmful if inhaled.                           |
| H336  | May cause drowsiness or dizziness.            |
| H351  | Suspected of causing cancer.                  |
| H361d | Suspected of damaging the unborn child.       |

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

### End of safety data sheet