

## Zar Interior Stain - Colormatcher Tint Base (Master)

Version number: REV 2.0

Revision: 2024-06-07

Replaces version of: 2024-06-05 (REV 1)

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name

**Zar Interior Stain - Colormatcher Tint Base (Master)**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

general use

#### 1.3 Details of the supplier of the safety data sheet

Sika Corporation

1396 Jefferson Avenue

Dunmore PA 18509

United States

Telephone: +1 (570) 344-1202

Telefax: (570) 969-7634

e-mail:

retailorders@us.sika.com

Website: <http://www.zar.com/>

e-mail (competent person)

crossley.robin@us.sika.com

#### 1.4 Emergency telephone number

Emergency information service

1-800-424-9300 Chemtrec (NORTH AMERICA)  
Emergency telephone number: outside office hours

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.4S	skin sensitization	1	Skin Sens. 1	H317
A.6	carcinogenicity	1B	Carc. 1B	H350
A.7	reproductive toxicity	1B	Repr. 1B	H360D
A.10	aspiration hazard	1	Asp. Tox. 1	H304
B.6	flammable liquid	3	Flam. Liq. 3	H226

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

#### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word

danger

- Pictograms

GHS02, GHS07, GHS08





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Zar Interior Stain - Colormatcher Tint Base (Master)

Version number: REV 2.0

Revision: 2024-06-07

Replaces version of: 2024-06-05 (REV 1)

### - Hazard statements

H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H350	May cause cancer.
H360D	May damage the unborn child.

### - Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308+P313	If exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

### - Hazardous ingredients for labelling

Distillates (petroleum), hydrotreated light, ethyl methyl ketoxime, 1-methyl-2-pyrrolidinone, Kerosene

## 2.3 Other hazards

### Hazards not otherwise classified

Contains ethyl methyl ketoxime. May produce an allergic reaction.  
May be harmful in contact with skin (GHS category 5: acutely toxic - dermal).  
Toxic to aquatic life with long lasting effects (GHS category 2: aquatic toxicity - acute and/or chronic).  
Causes mild skin irritation (GHS category 3: irritant to skin).

### Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0.1\%$ .

### Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of  $\geq 0.1\%$ .

## Zar Interior Stain - Colormatcher Tint Base (Master)

Version number: REV 2.0

Revision: 2024-06-07

Replaces version of: 2024-06-05 (REV 1)

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Not relevant (mixture)

#### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
Distillates (petroleum), hydro-treated light	CAS No 64742-47-8	25 – < 50	Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
Kerosene	CAS No 8008-20-6	5 – < 10	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
2-ethylhexanoic acid	CAS No 149-57-5	0.05 – < 1	Repr. 2 / H361d
ethyl methyl ketoxime	CAS No 96-29-7	0.05 – < 1	Acute Tox. 3 / H301 Acute Tox. 4 / H312 Acute Tox. 3 / H331 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Skin Sens. 1 / H317 Carc. 1B / H350 STOT SE 1 / H370 STOT SE 3 / H336 STOT RE 2 / H373 Flam. Liq. 4 / H227
1-methyl-2-pyrrolidinone	CAS No 872-50-4	0.05 – < 1	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Repr. 1B / H360D STOT SE 3 / H335 Flam. Liq. 4 / H227

#### Remarks

For full text of abbreviations: see SECTION 16

### SECTION 4: First-aid measures

#### 4.1 Description of first-aid measures

##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

##### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

##### Following skin contact

Wash with plenty of soap and water.

##### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

##### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

## Zar Interior Stain - Colormatcher Tint Base (Master)

Version number: REV 2.0

Replaces version of: 2024-06-05 (REV 1)

Revision: 2024-06-07

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media

Water jet

### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO<sub>x</sub>), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Zar Interior Stain - Colormatcher Tint Base (Master)

Version number: REV 2.0

Replaces version of: 2024-06-05 (REV 1)

Revision: 2024-06-07

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	2-ethylhexanoic acid	149-57-5	TLV®		5					iv	ACGIH® 2024
US	Kerosine (petroleum)	8008-20-6	REL		100 (10 h)						NIOSH REL

## Zar Interior Stain - Colormatcher Tint Base (Master)

Version number: REV 2.0

Revision: 2024-06-07

Replaces version of: 2024-06-05 (REV 1)

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Notation	Source
US	Kerosine (petroleum) (jet fuels, JP 5)	8008-20-6	TLV®		200					vap, Hy-Carb, MX-P, H	ACGIH® 2024
US	N-methyl-pyrrolidone (NMP) (1-methyl-2-pyrrolidone) (N-methyl-2-pyrrolidone)	872-50-4	PEL (CA)	1	4					H	Cal/ OSHA PEL

### Notation

Ceiling-C	ceiling value is a limit value above which exposure should not occur
H	absorbed through the skin
HyCarb	calculated as hydrocarbons
iv	inhalable fraction and vapor
MX-P	application restricted to conditions where exposure to aerosols is negligible
STEL	short-term exposure limit; a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours
vap	time-weighted average (unless otherwise specified as vapors)

Biological limit values						
Country	Name of agent	Parameter	Notation	Identifier	Value	Source
US	N-methyl-2-pyrrolidone	5-hydroxy-N-methyl-2-pyrrolidone		BEI®	100 mg/l	ACGIH® 2024

## 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## Zar Interior Stain - Colormatcher Tint Base (Master)

Version number: REV 2.0

Replaces version of: 2024-06-05 (REV 1)

Revision: 2024-06-07

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

##### Appearance

Physical state	liquid
Color	not determined
Particle	not relevant (liquid)
Odor	characteristic

##### Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	≥146 °C at 101.3 kPa
Flash point	38 °C at 1 atm
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	≤3.7 kPa at 37.8 °C
Density	not determined
Vapor density	this information is not available
Relative density	information on this property is not available
Solubility(ies)	not determined

##### Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	220 °C (auto-ignition temperature (liquids and gases))

##### Viscosity

- Dynamic viscosity	50 – 53 cP at 20 °C
Explosive properties	none
Oxidizing properties	none

## Zar Interior Stain - Colormatcher Tint Base (Master)

Version number: REV 2.0

Replaces version of: 2024-06-05 (REV 1)

Revision: 2024-06-07

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### 10.5 Incompatible materials

Oxidizers

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful in contact with skin.

Acute toxicity estimate (ATE) of components			
Name of substance	CAS No	Exposure route	ATE
ethyl methyl ketoxime	96-29-7	dermal	>1,000 mg/kg
ethyl methyl ketoxime	96-29-7	inhalation: vapor	>4.83 mg/l/4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.



## Zar Interior Stain - Colormatcher Tint Base (Master)

Version number: REV 2.0

Revision: 2024-06-07

Replaces version of: 2024-06-05 (REV 1)

### Respiratory or skin sensitization

May cause an allergic skin reaction.

### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

May cause cancer.

### Reproductive toxicity

May damage the unborn child.

### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### Aspiration hazard

May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated light	64742-47-8	LL50	5 mg/l	fish	96 h
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	1.4 mg/l	aquatic invertebrates	48 h
Kerosene	8008-20-6	LL50	5 mg/l	fish	96 h
Kerosene	8008-20-6	EL50	1.4 mg/l	aquatic invertebrates	48 h
2-ethylhexanoic acid	149-57-5	LC50	>100 mg/l	fish	96 h
2-ethylhexanoic acid	149-57-5	ErC50	49.3 mg/l	algae	72 h
ethyl methyl ketoxime	96-29-7	LC50	>100 mg/l	fish	96 h
ethyl methyl ketoxime	96-29-7	EC50	201 mg/l	aquatic invertebrates	48 h
ethyl methyl ketoxime	96-29-7	ErC50	11.8 mg/l	algae	72 h
1-methyl-2-pyrrolidinone	872-50-4	LC50	>500 mg/l	fish	96 h
1-methyl-2-pyrrolidinone	872-50-4	EC50	>1,000 mg/l	aquatic invertebrates	24 h
1-methyl-2-pyrrolidinone	872-50-4	ErC50	600.5 mg/l	algae	72 h

## Zar Interior Stain - Colormatcher Tint Base (Master)

Version number: REV 2.0

Revision: 2024-06-07

Replaces version of: 2024-06-05 (REV 1)

### Aquatic toxicity (chronic) of components

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	0.89 mg/l	aquatic invertebrates	21 d
Kerosene	8008-20-6	EL50	0.89 mg/l	aquatic invertebrates	21 d
2-ethylhexanoic acid	149-57-5	EC50	75 mg/l	aquatic invertebrates	21 d
ethyl methyl ketoxime	96-29-7	EC50	≥100 mg/l	aquatic invertebrates	21 d

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance at a concentration of ≥ 0.1%.

### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of ≥ 0.1%.

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## Zar Interior Stain - Colormatcher Tint Base (Master)

Version number: REV 2.0

Revision: 2024-06-07

Replaces version of: 2024-06-05 (REV 1)

### SECTION 14: Transport information

#### 14.1 UN number

DOT	UN 1993
IMDG-Code	UN 1993
ICAO-TI	UN 1993

#### 14.2 UN proper shipping name

DOT	Combustible liquid, n.o.s.
IMDG-Code	FLAMMABLE LIQUID, N.O.S.
ICAO-TI	Flammable liquid, n.o.s.
Technical name (hazardous ingredients)	Distillates (petroleum), hydrotreated light, Kerosene

#### 14.3 Transport hazard class(es)

DOT	3
IMDG-Code	3
ICAO-TI	3

#### 14.4 Packing group

DOT	III
IMDG-Code	III
ICAO-TI	III

#### 14.5 Environmental hazards

	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment)	Distillates (petroleum), hydrotreated light

#### 14.6 Special precautions for user

There is no additional information.

#### 14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

### Information for each of the UN Model Regulations

#### Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN1993, Combustible liquid, n.o.s., (contains: Distillates (petroleum), hydrotreated light, Kerosene), 3, III, environmentally hazardous
Reportable quantity (RQ)	4,236,570 lbs (1,923,403 kg) (naphthalene) (Ethylbenzene)
Danger label(s)	fish and tree
Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	148, IB3, T1, TP1
ERG No	128

## Zar Interior Stain - Colormatcher Tint Base (Master)

Version number: REV 2.0

Revision: 2024-06-07

Replaces version of: 2024-06-05 (REV 1)

### International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant YES (hazardous to the aquatic environment) (Distillates (petroleum), hydrotreated light)

Danger label(s) 3, fish and tree



Special provisions (SP) 223, 274, 955

Excepted quantities (EQ) E1

Limited quantities (LQ) 5 L

EmS F-E, S-E

Stowage category A

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Environmental hazards YES (hazardous to the aquatic environment)

Danger label(s) 3



Special provisions (SP) A3

Excepted quantities (EQ) E1

Limited quantities (LQ) 10 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

#### National regulations (United States)

**Toxic Substance Control Act (TSCA)** not all ingredients are listed (ACTIVE)

#### Superfund Amendment and Reauthorization Act (SARA TITLE III )

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
1-methyl-2-pyrrolidinone	872-50-4		1994-12-31

#### Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Kerosene	8008-20-6		ATSDR Neurotoxicants
Kerosene			ATSDR Neurotoxicants
ethyl methyl ketoxime	96-29-7		EC Annex VI CMRs - Cat. 1B
1-methyl-2-pyrrolidinone	872-50-4		EC Annex VI CMRs - Cat. 1B Prop 65

## Zar Interior Stain - Colormatcher Tint Base (Master)

Version number: REV 2.0

Revision: 2024-06-07

Replaces version of: 2024-06-05 (REV 1)

### - Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
1-methyl-2-pyrrolidinone	872-50-4				1.0 %

### - Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Kerosene	8008-20-6		F2
2-ethylhexanoic acid	149-57-5		
1-methyl-2-pyrrolidinone	872-50-4		TE F2

#### Legend

F2 Flammable - Second Degree  
TE Teratogenic

### - Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
KEROSINE (PETROLEUM)	8008-20-6	

### - Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
Kerosene	8008-20-6	F

#### Legend

F Flammability (NFPA®)

### California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
naphthalene	91-20-3		cancer
ethylbenzene	100-41-4		cancer
N-methylpyrrolidone	872-50-4		developmental

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Zar Interior Stain - Colormatcher Tint Base (Master)

Version number: REV 2.0

Revision: 2024-06-07

Replaces version of: 2024-06-05 (REV 1)

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

### National inventories

Country	Inventory	Status
AU	AIIC	not all ingredients are listed
CA	DSL	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed
VN	NCI	not all ingredients are listed
US	TSCA	not all ingredients are listed

#### Legend

AIIC Australian Inventory of Industrial Chemicals  
CICR Chemical Inventory and Control Regulation  
CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Zar Interior Stain - Colormatcher Tint Base (Master)

Version number: REV 2.0

Revision: 2024-06-07

Replaces version of: 2024-06-05 (REV 1)

### Legend

DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information, including date of preparation or last revision

### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200): change in the listing (table)	yes
2.2		- Hazard statements: change in the listing (table)	yes
2.2		- Precautionary statements: change in the listing (table)	yes
3.2		Description of the mixture: change in the listing (table)	yes
7.2	- Ventilation requirements: Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.	- Ventilation requirements: Use local and general ventilation. Ground/bond container and receiving equipment.	yes
9.1	Viscosity: not determined	Viscosity	yes
9.1		Dynamic viscosity: 50 – 53 cP at 20 °C	yes
11.1	Acute toxicity: Harmful if inhaled.GHS of the United Nations, annex 4: May be harmful in contact with skin.	Acute toxicity: Shall not be classified as acutely toxic.GHS of the United Nations, annex 4: May be harmful in contact with skin.	yes
11.1		- Acute toxicity estimate (ATE): change in the listing (table)	yes
11.1		Acute toxicity estimate (ATE) of components: change in the listing (table)	yes
14.1	DOT: UN 1992	DOT: UN 1993	yes
14.1	IMDG-Code: UN 1992	IMDG-Code: UN 1993	yes
14.1	ICAO-TI: UN 1992	ICAO-TI: UN 1993	yes

# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Zar Interior Stain - Colormatcher Tint Base (Master)

Version number: REV 2.0

Revision: 2024-06-07

Replaces version of: 2024-06-05 (REV 1)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.2	DOT: Flammable liquid, toxic, n.o.s.	DOT: Combustible liquid, n.o.s.	yes
14.2	IMDG-Code: FLAMMABLE LIQUID, TOXIC, N.O.S.	IMDG-Code: FLAMMABLE LIQUID, N.O.S.	yes
14.2	ICAO-TI: Flammable liquid, toxic, n.o.s.	ICAO-TI: Flammable liquid, n.o.s.	yes
14.2	Technical name (hazardous ingredients): Distillates (petroleum), hydrotreated light, ethyl methyl ketoxime	Technical name (hazardous ingredients): Distillates (petroleum), hydrotreated light, Kerosene	yes
14.3	DOT: 3 (6.1)	DOT: 3	yes
14.3	IMDG-Code: 3 (6.1)	IMDG-Code: 3	yes
14.3	ICAO-TI: 3 (6.1)	ICAO-TI: 3	yes
14.7	Particulars in the shipper's declaration: UN1992, Flammable liquid, toxic, n.o.s., (contains: Distillates (petroleum), hydrotreated light, ethyl methyl ketoxime), 3 (6.1), III, environmentally hazardous	Particulars in the shipper's declaration: UN1993, Combustible liquid, n.o.s., (contains: Distillates (petroleum), hydrotreated light, Kerosene), 3, III, environmentally hazardous	yes
14.7	Danger label(s): 3+6.1, fish and tree	Danger label(s): fish and tree	yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): B1, IB3, T7, TP1, TP28	Special provisions (SP): 148, IB3, T1, TP1	yes
14.7	ERG No: 131	ERG No: 128	yes
14.7	Danger label(s): 3+6.1, fish and tree	Danger label(s): 3, fish and tree	yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): 223, 274	Special provisions (SP): 223, 274, 955	yes
14.7	EmS: F-E, S-D	EmS: F-E, S-E	yes
14.7	Danger label(s): 3+6.1	Danger label(s): 3	yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Limited quantities (LQ): 2 L	Limited quantities (LQ): 10 L	yes
16		List of relevant phrases (code and full text as stated in section 2 and 3): change in the listing (table)	yes

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Zar Interior Stain - Colormatcher Tint Base (Master)

Version number: REV 2.0

Revision: 2024-06-07

Replaces version of: 2024-06-05 (REV 1)

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H360D	May damage the unborn child.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

### End of safety data sheet