#### MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ZAR DECK & SIDING CLEAR WOOD SEALER / NATURAL TONER HMIS CODES: H F R

PRODUCT CODE: 758 1 0 0

# SECTION 1 - MANUFACTURER IDENTIFICATION

MANUFACTURE'S NAME: UNITED GILSONITE LABORATORIES EMERGENCY PHONE: (800) 424-9300

1396 JEFFERSON AVENUE ADDRESS:

SCRANTON, PA 18509 INFORMATION PHONE: (570) 344-1202

NAME OF PREPARER: R. BARAKO

DATE ISSUED: FEBRUARY 2009

#### SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

HAZARDOUS COMPONENTS	CAS NUMBER	OCCUPATIONA OSHA PEL	L EXPOSURE LIMIT ACGIH TLV	TS OTHER	VAPOR PRESSURE mmHg@TEMP	WEIGHT PERCENT
WATER ACRYLIC POLYMER MATTING ADDITIVE PROPYLENE GLYCOL DISPERSED COLORANT	7732-18-5 N/A N/A 57-55-6 N/A	NOT ESTAB NOT ESTAB NOT ESTAB NOT ESTAB NOT ESTAB	NOT ESTAB NOT ESTAB NOT ESTAB NOT ESTAB NOT ESTAB	NOT ESTA NOT ESTA NOT ESTA NOT ESTA	AB N/A AB N/A AB 0.2 (68F)	65-67 15-20 7-10 <5 <5

No toxic chemical(s) subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372 are present.

# SECTION III - PHYSICAL/CHEMCIAL CHARACTERISTICS

SPECIFIC GRAVITY (H20 =1) 1.03

**BOILING RANGE:** 212 (F) **VAPOR DENSITY:** HEAVIER THAN AIR **EVAPORATION RATE:** SLOWER THAN ETHER

COATING VOC: LESS THAN 100 g/l **SOLUBILITY IN WATER: SOLUBLE** 

APPEARANCE AND ODOR: MILKY / REDISH TYPICAL AMINE ODOR

# SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASHPOINT: N/A METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME: **LOWER:** 0.6% **UPPER:** 12.5%

**EXTINGUISHING MEDIA:** NONE KNOWN

SPECIAL FIRE FIGHTING PROCEDURES: CONTAINER MAY SWELL AND BURST DURING A FIRE DUE TO INTERNAL PRESSURE CAUSED BY

HEAT. THIS MAY CAUSE A SLIPPERY CONDITION ON FLOORS

UNUSUAL FIRE AND EXPLOSION HAZARDS: N/A

### SECTION V - REACTIVITY DATA

STABILITY: PRODUCT IS STABLE

CONDITIONS TO AVOID: TEMPERATURES BELOW 32 (F) FOR STORAGE. TEMPERATURES BELOW 50 (F) FOR APPLICATION

INCOMPATIBILITY (MATERIALS TO AVOID): N/A

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: N/A

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

#### SECTION VI – HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: IN IT'S WET STATE, THIS PRODUCT SHOULD NOT POSE ANY THREAT TO HEALTH DUE TO OVEREXPOSURE

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: DIRECT CONTACT MAY CAUSE BURNING, TEARING, REDNESS AND SWELLING

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: CAN CAUSE SLIGHT IRRITATION

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: MAY PRODUCE SIGNS OF INTOXICATION CHARACTERIZED BY INCOORDINATION, DIZZINESS, DROWSINESS, HEADACHE, NAUSEA, MENTAL CONFUSION DEPENDING ON THE QUANTITY OF MATERIAL INGESTED

**HEALTH HAZARDS (ACUTE AND CHRONIC): NONE KNOWN** 

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: INHALATION OF THE SPRAYED MATERIAL OR THE DUST FROM SANDING THE DRY FILM CAN AGGRAVATE RESPIRATORY CONDITIONS

#### EMERGENCY AND FIRST AID PROCEDURES:

EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN IF IRRITATION PERSISTS

SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. CONSULT A PHYSICIAN IF IRRITATION PERSISTS

INGESTION: SEEK MEDICAL ATTENTION. IF INDIVIDUAL IS DROWSY OR UNCONSCIOUS, DO NOT GIVE ANYTHING BY MOUTH; PLACE INDIVIDUAL ON THE LEFT SIDE WITH HEAD DOWN. CONTACT A PHYSICIAN, MEDICAL FACILITY OR POISON CONTROL CENTER FOR ADVICE ABOUT WHETHER TO INDUCE VOMITING

INHALATION: REMOVE VICTIM TO FRESH AIR

#### SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: DIKE AREA AROUND SPILL. APPLY ABSORBENT MATERIAL, THEN SWEEP UP AND PLACE IN PROPER CONTAINERS

WASTE DISPOSAL METHOD: DISPOSE OF IN APPROVED SITES ACCORDING TO LOCAL, STATE AND FEDRAL REGULATIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: AVOID BREATHING SANDING DUST. KEEP FROM FREEZING. STORE MATERIAL IN AREAS WHERE TEMPERATURES RANGE FROM 50 (F) TO 90 (F)

OTHER PRECAUTIONS: N/A

## SECTIONS VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: WHEN SPRAYING OR SANDING DRY FILM, USE NIOSH APPROVED RESPIRATOR WITH DUST PARTICLE AND ORGANIC VAPOR CARTRIDGES

**VENTILATION:** USE ADEQUATE VENTILATION IN VOLUME AND PATTERN TO MAINTAIN EXPOSURE LEVELS BELOW THAT LISTED IN SECTION II

PROTECTIVE GLOVES: USE NEOPRENE RUBBER GLOVES TO PREVENT SKIN CONTACT

EYE PROTECTION: USE SAFETY EYEWEAR WITH SPLASH GUARDS

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE

WORK / HYGIENIC PRACTICES: WASH HANDS BEFORE EATING, SMOKING OR USING WASH ROOM

# SECTION IX - DISCLAIMER

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.