



BUILDING TRUST



PROVISIONAL PRODUCT DATA SHEET 2026-06-15

ZAR® Exterior Oil Base Poly

Exterior Oil Base Polyurethane Ultraviolet

DESCRIPTION

CSI Masterformat® 09 93 13

ZAR® Exterior Oil Base Poly is an incredibly fast-drying, oil-based, clear wood polyurethane finish that can be recoated in only 2 hours. Formulated with ultraviolet radiation absorbers and antioxidants, it's specifically formulated to protect exterior surfaces that are subjected to direct sunlight.

USES

Ideal for woodwork and wood marine surfaces (above water-line), patio furniture, and exterior doors made of wood, metal, or fiberglass

CHARACTERISTICS / ADVANTAGES

CERTIFICATES AND TEST REPORTS

PROVISIONAL PRODUCT DATA SHEET 2026-06-15

ZAR® Exterior Oil Base Poly

June 2026, Version 01.01

021890100000000210

THE PRODUCT DESCRIBED IN THIS PRODUCT DATA SHEET (PDS) IS STILL UNDER DEVELOPMENT AND HAS NEITHER BEEN FINALLY RELEASED NOR CERTIFIED. THIS PDS MUST NOT BE USED FOR THE APPLICATION OF THE PRODUCT. SIKA MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE PERFORMANCE, QUALITY OR OTHER CHARACTERISTICS OF THE PRODUCT.

PRODUCT INFORMATION

Composition	Oil Base				
Packaging	Size	PC/Case	Sheen	Order No.	Old Order No.
	1 quart	4	Gloss	832715	34012
	1 gallon	2	Gloss	832716	34013
	1 quart	4	Satin	832718	34112
	1 gallon	2	Satin	832719	34113
Available in 2 attractive sheens					
Appearance / Color	Gloss 90 + @ 60° Satin 45 ± 3 @ 60°				
Shelf life	3 years in original, unopened container				
Storage conditions	Avoid heat, sparks, open flame, and other ignition sources. Store in a cool, dry, well-ventilated area between 40°F (4°C) and 90°F (32°C). Avoid freezing and prolonged exposure to direct sunlight or high temperatures.				
Density	Lbs./US gal. 7.45 ± 2 (SG 0.89)				
Thickness	2 wet mils per coat				
Flash point	104°F (40°C)				
Solid content	% weight solids: 45 ± 1				
Number of Coats	500 to 600 sq. ft. (46 m2 - 55.7 m2) / gal. 3 coats minimum recommended Note: Actual coverage will vary depending upon application method, surface texture, and porosity.				
Ambient air temperature	For best results, apply when air and surface temperatures are above 50°F (10°C). Avoid using in direct sunlight or within 1 hour of dusk, as dew will dull the finish.				
Substrates	New Wood: Sand smooth using fine sandpaper (120-150 grit). Remove sanding dust with a tack cloth or a cloth dampened with mineral spirits. Old Clear Finishes in Good Condition: Remove grease, dirt, and wax. Sand lightly in the direction of the grain to remove any gloss. Clean sanding dust with a tack cloth or cloth dampened with mineral spirits. Old Clear Finishes in Poor Condition: Remove completely. If the old finish contains wax, remove it completely regardless of condition. Sand and re-				

PROVISIONAL PRODUCT DATA SHEET
2026-06-15
ZAR® Exterior Oil Base Poly
June 2026, Version 01.01
02189010000000210



BUILDING TRUST



move sanding dust with a tack cloth or a cloth dampened with mineral spirits.

Exterior Surfaces of Stained Steel or Fiberglass Entry Doors: DO NOT SAND. ZAR® Stain must be thoroughly dry.

NOTE: To ensure satisfactory results, always prepare a sample or test the product on an inconspicuous area to determine compatibility before completing the job.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

LIMITATIONS OF USE

Not recommended for use on decks or other areas subject to foot traffic.

APPLICATION INSTRUCTIONS

MIXING

Stirring is not required for Gloss. For Satin, stir thoroughly before and during application. DO NOT THIN. Do not shake!

APPLICATION

Apply straight from the can. Use a brush, lambswool applicator, or spray. Apply ZAR® Exterior Oil Base Poly in the direction of the grain and allow it to self-level. Avoid over-brushing, which may trap air bubbles in the finish and result in streaks.

Apply light, even strokes. If bubbles or runs occur, wipe clean with mineral spirits. Allow each coat to dry at least 2 hours. Drying time may vary due to temperature and humidity.

Sand lightly. (Do not sand fiberglass or wood-grained metal surfaces.) Remove sanding dust with a tack

cloth or a clean rag dampened with mineral spirits. Re-apply. Apply a minimum of three coats. Allow the final coat to dry 4-6 hours.

WARNING- If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Keep away from heat and flame. To prevent vapor buildup, open all windows and doors to achieve cross-ventilation.

DANGER - RAGS, STEEL WOOL, OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER USE, PLACE RAGS, STEEL WOOL, OR WASTE IN A SEALED, WATER-FILLED METAL CONTAINER.

MAINTENANCE INSTRUCTIONS

CLEANING

Mineral Spirits

MAINTENANCE

Exterior durability depends on the amount of exposure to the sun and weathering conditions. Inspect the finish yearly for signs of wear. If minimum deteriora-

PROVISIONAL PRODUCT DATA SHEET

2026-06-15

ZAR® Exterior Oil Base Poly

June 2026, Version 01.01

02189010000000210



BUILDING TRUST



tion has occurred, wipe the surface with mineral spirits, sand lightly with fine sandpaper, and apply another coat.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at www.zar.com or by calling SIKA's Technical Service Department at 1-800-272-3235, option 2. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR**

IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/about-us/terms-conditions-of-sale.html> or by calling 1-800-272-3235, option 2.

PROVISIONAL PRODUCT DATA SHEET

2026-06-15

ZAR® Exterior Oil Base Poly

June 2026, Version 01.01

021890100000000210

