

acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15 Replaces version of: 2023-11-17 (REV 2)

SECTION 1: Identification

1.1 Product identifier

Trade name ZAR® Wood Patch - Golden Oak

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses fille

paint related material

1.3 Details of the supplier of the safety data sheet

Sika Corporation

1396 Jefferson Avenue Dunmore PA 18509 United States

Telephone: +1 (570) 344-1202 Telefax: (570) 969-7634

e-mail:

retailorders@us.sika.com Website: http://www.zar.com/

e-mail (competent person) crossley.robin@us.sika.com

1.4 Emergency telephone number

Emergency information service 1-800-424-9300 Chemtrec (NORTH AMERICA)

Emergency telephone number: outside office

hours

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
A.4R	respiratory sensitization	1	Resp. Sens. 1	H334
A.4S	skin sensitization	1	Skin Sens. 1	H317
A.6	carcinogenicity	1A	Carc. 1A	H350
A.7	reproductive toxicity	1B	Repr. 1B	H360F

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS08



- Hazard statements

H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H350 May cause cancer.

United States: en Page: 1 / 18



acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15 Replaces version of: 2023-11-17 (REV 2)

H360F May damage fertility.

United States: en Page: 2 / 18



acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15

Replaces version of: 2023-11-17 (REV 2)

- Precautionary statements

P201 Obtain special instructions before use.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P272 Contaminated work clothing must not be allowed out of the workplace.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P285 In case of inadequate ventilation wear respiratory protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for

breathing.

P308+P313 If exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling Wood Dust, Barium

Wood Dust, Barium diboron tetraoxide, Quartz (SiO2)

2.3 Other hazards

Special danger of slipping by leaking/spilling product.

Hazards not otherwise classified

Contains Wood Dust, 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of \geq 0.1%.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
Distillates (petroleum), hydro- treated light	CAS No 64742-47-8	1-<5	Acute Tox. 3 / H331 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
Wood Dust		0.05 – < 1	Resp. Sens. 1 / H334 Skin Sens. 1 / H317 Carc. 1A / H350 STOT SE 3 / H335 STOT RE 1 / H372 cD / OSHA003
Quartz (SiO2)	CAS No 14808-60-7	0.05 – < 1	Carc. 1A / H350
Barium diboron tetraoxide	CAS No 13701-59-2	0.05 – < 1	Acute Tox. 4 / H302 Acute Tox. 4 / H332 Eye Irrit. 2B / H320 Repr. 1B / H360F

United States: en Page: 3 / 18



acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15

Replaces version of: 2023-11-17 (REV 2)

Name of substance	Identifier	Wt%	Classification acc. to GHS
1,2-benzisothiazol-3(2H)-one	CAS No 2634-33-5	< 0.05	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Skin Sens. 1 / H317

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

United States: en Page: 4 / 18



acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15 Replaces version of: 2023-11-17 (REV 2)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as

frost

7.3 Specific end use(s)

See section 16 for a general overview.

United States: en Page: 5 / 18



acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15 Replaces version of: 2023-11-17 (REV 2)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Coun- try	Name of agent	CAS No	ldenti- fier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Nota- tion	Source
US	mica	12001-26-2	TLV®		0.1					r	ACGIH® 2023
US	mica	12001-26-2	PEL (CA)		3					r, less1sili ca	Cal/ OSHA PEL
US	mica	12001-26-2	REL		3 (10 h)					r, less1sili ca	NIOSH REL
US	silicates (less than 1% crystalline silica); mica	12001-26-2	PEL	706						less1sili ca, partml, r	29 CFR 1910.10 00
US	calcium carbonate	1317-65-3	REL		10 (10 h)					i, natur- al	NIOSH REL
US	calcium carbonate	1317-65-3	REL		5 (10 h)					r, nat- ural	NIOSH REL
US	limestone	1317-65-3	REL		10 (10 h)					i	NIOSH REL
US	limestone	1317-65-3	REL		5 (10 h)					r	NIOSH REL
US	limestone (calci- um carbonate)	1317-65-3	PEL		15					i, dust	29 CFR 1910.10 00
US	limestone (calci- um carbonate)	1317-65-3	PEL		5					r, dust	29 CFR 1910.10 00
US	quartz	14808-60-7	PEL (CA)		0.05					r	Cal/ OSHA PEL
US	silica, crystalline - quartz	14808-60-7	PEL		0.05					r	29 CFR 1910.10 00
US	silica, crystalline - quartz	14808-60-7	REL		0.05 (10 h)					r, appx- A	NIOSH REL

Notation

appx-A NIOSH Potential Occupational Carcinogen (Appendix A)

Ceiling-C ceiling value is a limit value above which exposure should not occur

dust as dust

i inhalable fraction

less1silica with less than 1 % free crystalline silica

natural natural partml particles/ml respirable fraction

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute peri-

od (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours

time-weighted average (unless otherwise specified

United States: en Page: 6 / 18



acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15 Replaces version of: 2023-11-17 (REV 2)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid (paste)
Color	Golden Oak
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	8.5
Melting point/freezing point	not determined
Initial boiling point and boiling range	≥146 °C at 101.3 kPa
Flash point	100 °C at 1 atm
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	≤3.7 kPa at 37.8 °C
Density	1.752 ^g / _{cm³} at 20 °C

United States: en Page: 7 / 18



acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15

Replaces version of: 2023-11-17 (REV 2)

Vapor density	this information is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	220 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

United States: en Page: 8 / 18



acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15 Replaces version of: 2023-11-17 (REV 2)

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
Distillates (petroleum), hydrotreated light	64742-47-8	inhalation: vapor	>5.28 ^{mg} / _l /4h
Barium diboron tetraoxide	13701-59-2	oral	850 ^{mg} / _{kg}
Barium diboron tetraoxide	13701-59-2	inhalation: dust/mist	1.5 ^{mg} /ı/4h
1,2-benzisothiazol-3(2H)-one	2634-33-5	oral	670 ^{mg} / _{kg}

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
Quartz (SiO2)	14808-60-7	1	

Legend

1 Carcinogenic to humans

Reproductive toxicity

May damage fertility.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

United States: en Page: 9 / 18



acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15 Replaces version of: 2023-11-17 (REV 2)

Aquatic toxicity (acute) of components

	•				
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated light	64742-47-8	LL50	5 ^{mg} / _l	fish	96 h
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	1.4 ^{mg} / _l	aquatic invertebrates	48 h
Barium diboron tetraox- ide	13701-59-2	LC50	62 ^{mg} / _l	fish	96 h
Barium diboron tetraox- ide	13701-59-2	EC50	20.3 ^{mg} / _I	aquatic invertebrates	48 h
Barium diboron tetraox- ide	13701-59-2	ErC50	7.8 ^{mg} / _l	algae	72 h
1,2-benzisothiazol-3(2H)- one	2634-33-5	LC50	16.7 ^{mg} / _l	fish	96 h
1,2-benzisothiazol-3(2H)- one	2634-33-5	EC50	2.94 ^{mg} / _l	aquatic invertebrates	48 h
1,2-benzisothiazol-3(2H)- one	2634-33-5	ErC50	150 ^{µg} / _l	algae	72 h

Aquatic toxicity (chronic) of components

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	0.89 ^{mg} / _l	aquatic invertebrates	21 d
Barium diboron tetraox- ide	13701-59-2	EC50	>100 ^{mg} / _I	microorganisms	3 h
1,2-benzisothiazol-3(2H)- one	2634-33-5	EC50	13 ^{mg} / _I	microorganisms	3 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of \geq 0.1%.

12.7 Other adverse effects

Data are not available.

United States: en Page: 10 / 18



acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15 Replaces version of: 2023-11-17 (REV 2)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance it-self.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number not subject to transport regulations

14.2 UN proper shipping name not relevant

14.3 Transport hazard class(es) none

14.4 Packing group not assigned

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG) - Additional information Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

Toxic Substance Control Act (TSCA) not all ingredients are listed (ACTIVE)

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Quartz (SiO2)	14808-60-7		IARC Carcinogens - 1

United States: en Page: 11 / 18



acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15 Replaces version of: 2023-11-17 (REV 2)

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE		De Minimis Concentration Threshold
Quartz (SiO2)		1095		1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Quartz (SiO2)		A, *	

Legend

* Substances which are regulated by OSHA as carcinogens; have been categorized by the ACGIH as either "human carcinogens" or "suspect of carcinogenic potential for man"; have been evaluated by the International Agency for Research on Cancer (IARC) and found to be carcinogens or potential carcinogens; or have been listed as a carcinogen or potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP).

the Annual Report on Carcinogens published by the National Toxicology Program (NTP).

A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Quartz (SiO2)	14808-60-7		CA

Legend

CA Carcinogenic

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
Quartz (SiO2)	14808-60-7	Т
Quartz (SiO2)	14808-60-7	Т

Legend

T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals					
Name acc. to inventory	CAS No	Remarks	Type of the toxicity		
silica, crystalline		airborne particles of respir- able size	cancer		
titanium dioxide	13463-67-7	airborne, unbound particles of respirable size	cancer		
carbon black	1333-86-4	airborne, unbound particles of respirable size	cancer		
Talc containing asbestiform fibers	14807-96-6	Talc containing asbestiform fibers	cancer		
ethylene glycol (ethanediol)	107-21-1		developmental		
1,4-dioxane	123-91-1		cancer		
ethylene oxide	75-21-8		cancer		

United States: en Page: 12 / 18



acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15 Replaces version of: 2023-11-17 (REV 2)

Proposition 65 List of chemicals

Name acc. to inventory	CAS No	Remarks	Type of the toxicity
ethylene oxide	75-21-8		female
ethylene oxide	75-21-8		developmental, male
acetaldehyde	75-07-0		cancer

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	0	material that will not burn under typical fire conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	0	material that will not burn under typical fire conditions
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed or exempt from listing
AU	AIIC	not all ingredients are listed
CA	DSL	all ingredients are listed or exempt from listing
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed

United States: en Page: 13 / 18



acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15 Replaces version of: 2023-11-17 (REV 2)

Country **Inventory Status INSQ** not all ingredients are listed MX ΝZ NZIoC all ingredients are listed or exempt from listing **PICCS** all ingredients are listed or exempt from listing PH TR CICR not all ingredients are listed TW TCSI not all ingredients are listed VN NCI not all ingredients are listed

Legend

Australian Inventory of Industrial Chemicals
Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS)
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China AIIC CICR

CSCL-ENCS

DSL

ECSI

IECSC

INSQ National Inventory of Chemical Substances

ISHA-ENCS Inventory of Existing and New Chemical Substances (ISHA-ENCS)

KECI Korea Existing Chemicals Inventory National Chemical Inventory New Zealand Inventory of Chemicals NCI NZIoC

Philippine Inventory of Chemicals and Chemical Substances (PICCS) PICCS

REACH Reg. REACH registered substances

TCSI TSCA Taiwan Chemical Substance Inventory

Toxic Substance Control Act

Chemical Safety Assessment 15.2

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-rel- evant
2.1		Classification acc. to OSHA "Hazard Communica- tion Standard" (29 CFR 1910.1200): change in the listing (table)	yes
2.1	The most important adverse physicochemical, human health and environmental effects: The product is combustible and can be ignited by potential ignition sources.		yes
2.2		- Pictograms: change in the listing (table)	yes
2.2		- Hazard statements: change in the listing (table)	yes
2.2		 Precautionary statements: change in the listing (table) 	yes
5.2	Special hazards arising from the substance or mixture: In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.	Special hazards arising from the substance or mixture	yes

United States: en Page: 14 / 18



acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15 Replaces version of: 2023-11-17 (REV 2)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-rel- evant
7.1	- Measures to prevent fire as well as aerosol and dust generation: Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.	- Measures to prevent fire as well as aerosol and dust generation: Use local and general ventilation. Use only in well-ventilated areas.	yes
7.1	Specific notes/details: Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.		yes
7.2	Managing of associated risks		yes
7.2	- Explosive atmospheres: Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.		yes
7.2	- Flammability hazards: Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static dis- charge. Protect from sunlight.		yes
7.2	- Ventilation requirements: Use local and general ventilation. Ground/bond container and receiving equipment.		yes
7.2	- Packaging compatibilities: Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.		yes
9.1	Flash point: 49 °C at 1 atm	Flash point: 100°C at 1 atm	yes
10.1	Reactivity: Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.	Reactivity: Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".	yes
10.1	If heated: Risk of ignition		yes
10.4	Conditions to avoid: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	Conditions to avoid: There are no specific conditions known which have to be avoided.	yes
10.4	Hints to prevent fire or explosion: Use explosion-proof electrical/ventilating/lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.		yes
13.1	Waste treatment-relevant information: Solvent reclamation/regeneration.		yes

United States: en Page: 15 / 18



acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15 Replaces version of: 2023-11-17 (REV 2)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-rel- evant
13.1	Waste treatment of containers/packages: Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied pack- ages can be recycled. Handle contaminated pack- ages in the same way as the substance itself.	Waste treatment of containers/packages: Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.	yes
14.1	UN number	UN number: not subject to transport regulations	yes
14.1	DOT: UN 1263		yes
14.1	IMDG-Code: UN 1263		yes
14.1	ICAO-TI: UN 1263		yes
14.2	DOT: Paint		yes
14.2	IMDG-Code: PAINT		yes
14.2	ICAO-TI: Paint		yes
14.3	DOT: 3		yes
14.3	IMDG-Code: 3		yes
14.3	ICAO-TI:		yes
14.4	DOT:		yes
14.4	IMDG-Code: III		yes
14.4	ICAO-TI:		yes
14.7	Particulars in the shipper's declaration: UN1263, Paint, 3, III		yes
14.7	Reportable quantity (RQ): 375,940 lbs (170,677 kg) (ammonia) (ethylene ox- ide)		yes
14.7	Danger label(s): 3		yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): 367, B1, B52, B131, IB3, T2, TP1, TP29		yes
14.7	ERG No: 128		yes
14.7	Marine pollutant: -		yes
14.7	Danger label(s): 3		yes

United States: en Page: 16 / 18



acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15 Replaces version of: 2023-11-17 (REV 2)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-rel- evant
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): 163, 223, 367, 955		yes
14.7	Excepted quantities (EQ): E1		yes
14.7	Limited quantities (LQ): 5 L		yes
14.7	EmS: F-E, <u>S-E</u>		yes
14.7	Stowage category: A		yes
14.7	Danger label(s): 3		yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): A3, A72, A192		yes
14.7	Excepted quantities (EQ): E1		yes
14.7	Limited quantities (LQ): 10 L		yes
14.2	UN proper shipping name	UN proper shipping name: not relevant	yes
14.3	Transport hazard class(es)	Transport hazard class(es): none	yes
14.4	Packing group	Packing group: not assigned	yes
14.7	Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information	Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information: Not subject to transport regulations.	yes
14.7	International Maritime Dangerous Goods Code (IMDG) - Additional information	International Maritime Dangerous Goods Code (IMDG) - Additional information: Not subject to IMDG.	yes
14.7	International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information	International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information: Not subject to ICAO-IATA.	yes
15.1		NPCA-HMIS® III: change in the listing (table)	yes
15.1		NFPA® 704: change in the listing (table)	yes

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

United States: en Page: 17 / 18



acc. to 29 CFR 1910.1200 App D

ZAR® Wood Patch - Golden Oak

Version number: REV 3.0 Revision: 2023-12-15 Replaces version of: 2023-11-17 (REV 2)

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text	
H226	Flammable liquid and vapor.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H320	Causes eye irritation.	
H331	Toxic if inhaled.	
H332	Harmful if inhaled.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H335	May cause respiratory irritation.	
H350	May cause cancer.	
H360F	May damage fertility.	
H372	Causes damage to organs through prolonged or repeated exposure.	
OSHA003	May form combustible dust concentrations in air.	

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

End of safety data sheet

United States: en Page: 18 / 18