

SAFETY DATA SHEET

Issuing Date No data available Revision Date 3-May-2019 Revision Number 3

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier 328-329-330-339

Product Name ZAR® Interior Oil Base Poly

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Clear Wood Finish - Varnish

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Sika Corporation **Supplier Address** Sika Gorporation 1396 Jefferson Ave.

Dunmore PA 18509 US

Supplier Phone Number Phone:570-344-1202

Fax:570-969-7634

Contact Phone:570-344-1202

Supplier Email retailorders@us.sika.c (800) 424-9300 Chemtrec

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 3

GHS Label elements, including precautionary statements

Emergency Overview

Signal word Danger

Hazard Statements

May cause genetic defects Suspected of causing cancer

May be fatal if swallowed and enters airways

Flammable liquid and vapor



Appearance Amber Physical State Liquid Odor Aliphatic hydrocarbons

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Skir

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

23.40396% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Harmful to aquatic life with long lasting effects PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

·

3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical Name	CAS No.	Weight-%	Trade Secret
Stoddard solvent	8052-41-3	60 - 100	*
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5	*
Kerosene	8008-20-6	1 - 5	*
Octanoic acid, cobalt salt	6700-85-2	0.1 - 1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Eye Contact If symptoms persist, call a physician. Rinse immediately with plenty of water, also under the

evelids, for at least 15 minutes. Keep eve wide open while rinsing. Do not rub affected area.

Remove contact lenses, if present and easy to do. Continue rinsing.

Skin Contact In the case of skin irritation or allergic reactions see a physician. Wash off immediately with

soap and plenty of water while removing all contaminated clothes and shoes.

Inhalation Remove to fresh air. If symptoms persist, call a physician. Aspiration into lungs can produce

severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. If not breathing, give artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Seek immediate medical attention/advice. Delayed

pulmonary edema may occur.

Ingestion Do NOT induce vomiting. Aspiration hazard if swallowed - can enter lungs and cause

damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an

unconscious person. Call a physician or poison control center immediately.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Wear

personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects

Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Because of the danger of aspiration, emesis or gastric lavage

should not be employed unless the risk is justified by the presence of additional toxic

substances.

·

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Unsuitable Extinguishing Media

Do not use a solid water stream as it may scatter and spread fire.

Specific Hazards Arising from the Chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Uniform Fire Code Combustible Liquid: II

Irritant: Liquid

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Ensure adequate ventilation. Use personal protective equipment as required. Evacuate

personnel to safe areas. See section 8 for more information. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled

material.

Other Information Refer to protective measures listed in Sections 7 and 8. Ventilate the area.

Environmental precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage

if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Do not touch or walk through spilled

material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill

to collect runoff water. Keep out of drains, sewers, ditches and waterways.

Methods for cleaning up

Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Keep away from

open flames, hot surfaces and sources of ignition. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Store locked up. Keep containers tightly closed in a dry, cool and well-ventilated place.

Protect from moisture. Keep out of the reach of children. Store away from other materials. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with

the particular national regulations. Store in accordance with local regulations.

Incompatible ProductsNone known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

·

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
Stoddard solvent	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m ³	
8052-41-3		TWA: 2900 mg/m ³	Ceiling: 1800 mg/m ³ 15 min	
		(vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	TWA: 350 mg/m ³	
Silica, amorphous, fumed, crystal-free 112945-52-5	10 mg/m ³	TWA: 20 mppcf; ((80)/(% SiO2) mg/m³)	IDLH: 3000 mg/m ³ TWA: 6 mg/m ³	
Kerosene	TWA: 200 mg/m ³ total	-	TWA: 100 mg/m ³	
8008-20-6	hydrocarbon vapor application			
	restricted to conditions in which			
	there are negligible aerosol			
	exposures			
	S*			

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Tight sealing safety goggles.

Skin and Body Protection Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant

apron. Impervious gloves. Antistatic boots.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene MeasuresHandle in accordance with good industrial hygiene and safety practice. Do not eat, drink or

smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace.

Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State Liquid

AppearanceAmberOdorAliphatic hydrocarbonsColorNo information availableOdor ThresholdNo information available

Property Values Remarks/ Method

UNKNOWN None known Melting / freezing point No data available None known Boiling point / boiling range None known No data available Flash Point 40 C / 104 F None known **Evaporation Rate** No data available None known Flammability (solid, gas) No data available None known Flammability Limit in Air

Upper flammability limitNo data availableLower flammability limitNo data available

Vapor pressure No data available None known Vapor density No data available None known **Specific Gravity** No data available None known Water Solubility Slightly soluble None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known No data available Autoignition temperature None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known Dynamic viscosity No data available None known **Explosive properties** No data available

No data available

Other Information

Oxidizing Properties

Softening PointNo data availableVOC Content (%)No data availableParticle SizeNo data availableParticle Size DistributionNo data available

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

.

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can

produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be

fatal. May cause irritation of respiratory tract.

Eye Contact Specific test data for the substance or mixture is not available. May cause irritation.

Skin Contact Repeated exposure may cause skin dryness or cracking.

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema

and pneumonitis. May be fatal if swallowed and enters airways.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Kerosene 8008-20-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat)4 h

Information on toxicological effects

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Asthma-like and/ or skin allergy-like

symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects There is no data available for this product. Contains a known or suspected mutagen.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Silica, amorphous, fumed, crystal-free 112945-52-5		Group 3		
Kerosene 8008-20-6	A3	Group 3		
Octanoic acid, cobalt salt 6700-85-2		Group 2B		Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposureNo information available.

Chronic ToxicityContains a known or suspected mutagen. Possible risk of irreversible effects. Contains a

known or suspected carcinogen. Aspiration may cause pulmonary edema and pneumonitis.

Target Organ Effects May affect the genetic material in germ cells (sperm and eggs). Respiratory system. Eyes.

Skin. Gastrointestinal tract (GI). Central Nervous System (CNS). Kidney. Liver. Testes.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

Not applicable

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methodsThis material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number D001

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Octanoic acid, cobalt salt 6700-85-2	Toxic

14. TRANSPORT INFORMATION

DOTNOT REGULATED (If shipped in NON BULK packaging by ground transport)

Proper Shipping Name NON-REGULATED

Hazard Class N/A Emergency Response Guide 128

Number

<u>TDG</u>

UN-No. UN1263
Proper Shipping Name PAINT
Hazard Class 3
Packing Group III

Description UN1263, PAINT, 3, III

MEX

UN-No. UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group III

Description UN1263 Paint,3,III

ICAO

UN-No.UN1263Proper Shipping NamePaintHazard Class3Packing GroupIII

Description UN1263,Paint,3,PG III

<u>IATA</u>

UN-No. UN1263
Proper Shipping Name PAINT
Hazard Class 3
Packing Group III

Description UN1263,Paint,3,PG III

IMDG/IMO

VN-No.UN1263Proper Shipping NamePaintHazard Class3Packing GroupIIIEmS No.F-E, S-E

Description UN1263, Paint,3,PG III, FP 40C

RID

UN-No.UN1263Proper Shipping NamePaintHazard Class3Packing GroupIIIClassification codeF1

Description UN1263 Paint,3,III

<u>ADR</u>

UN-No. UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group III
Classification code F1

Description UN1263 Paint,3,III

<u>ADN</u>

UN-No. UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group III
Classification code F1

Special Provisions 163, 640H, 650 **Description** UN1263 Paint,3,III

Hazard Labels3Limited QuantityLQ7VentilationVE01

Page 10 / 12

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health HazardYesChronic Health HazardYesFire HazardYesSudden release of pressure hazardNoReactive HazardNo

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Stoddard solvent	X	X	Χ		
8052-41-3					
Kerosene	X	X	Χ		
8008-20-6					
Octanoic acid, cobalt salt			Χ	X	X
6700-85-2					

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Stoddard solvent		Mexico: TWA 100 ppm
8052-41-3 (60 - 100)		Mexico: TWA 523 mg/m ³
		Mexico: STEL 200 ppm
		Mexico: STEL 1050 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada WHMIS Hazard Class

B3 - Combustible liquid D2A - Very toxic materials D2B - Toxic materials



16. OTHER INFORMATION

NFPA Health Hazards 2 Flammability 2 Instability 0 Physical and Chemical Hazards -

HMIS Health Hazards 2 * Flammability 2 Physical Hazard 0 Personal Protection X

Chronic Hazard Star Legend *= Chronic Health Hazard

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Revision Date 23-Jul-2014

Revision NoteNo information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet