



BUILDING TRUST



PRODUCT DATA SHEET

ZAR® Interior Oil Base Stain

Interior oil base, multi-surface, full-bodied, translucent wiping stain

DESCRIPTION

ZAR® Interior Oil Base Stain is a highly pigmented oil base stain uniquely formulated to achieve a rich, luxurious color in one coat. It's thick viscosity allows for an easy application resulting in a rich uniform color. This stain is formulated with "controlled penetration" for uniform color without unsightly streaks or lap marks, it can be used on previously painted or varnished surfaces without stripping to achieve a gorgeous effect. It can also be used to stain decorative faux finishing and color toning on non-porous, non-wood surfaces.

USES

- Staining unfinished & previously finished wood
- Previously painted/varnished surfaces to achieve "wood grain effect"
 - Fiberglass / Metal / Composite
- Ideal for "hard to stain woods":
 - Pine / Birch / Alder / Maple
- Glazing on cabinets, moldings, & floors for a 2-tone layered effect

CHARACTERISTICS / ADVANTAGES

- Stains easily with controlled penetration
- Wipes on like furniture polish
- Produces a rich uniform color
- Leaves no lap marks or streaks
- Multi-surface formula

PRODUCT DATA SHEET

ZAR® Interior Oil Base Stain

September 2025, Version 01.01

020612000020223159

PRODUCT INFORMATION

Composition	Oil Base				
Packaging	Size	PC/Case	Color	Order No.	Old Order No.
	1/2 pint	6	Aged Bourbon	831093	11506
	1 quart	4	Aged Bourbon	831094	11512
	1/2 pint	6	Mocha	831432	11906
	1 quart	4	Mocha	831433	11912
	1/2 pint	6	Premium Teak	831434	12006
	1 quart	4	Premium Teak	831435	12012
	1/2 pint	6	Baby Grand	831436	12106
	1 quart	4	Baby Grand	831437	12112
	1/2 pint	6	Dark Choc. Truffle	831438	12306
	1 quart	4	Dark Choc. Truffle	831439	12312
	1/2 pint	6	Golden Sun-set	831440	12706
	1 quart	4	Golden Sun-set	831441	12712
	1/2 pint	6	Mink	831430	12806
	1 quart	4	Mink	831431	12812
	1/2 pint	6	Vintage Modern	831366	12906
	1 quart	4	Vintage Modern	831367	12912
	1/2 pint	6	Black Caviar	831368	13506
	1 quart	4	Black Caviar	831369	13512
	1/2 pint	6	Beach House	831452	13906
	1 quart	4	Beach House	831453	13912
	1/2 pint	6	Silk Gray	831450	17006
	1 quart	4	Silk Gray	831451	17012
	1/2 pint	6	Malibu Gray	831456	17106

PRODUCT DATA SHEET
ZAR® Interior Oil Base Stain
September 2025, Version 01.01
020612000020223159



BUILDING TRUST



1 quart	4	Malibu Gray	831457	17112
1/2 pint	6	Oiled Leather	831458	50306
1 quart	4	Oiled Leather	831459	50312
1/2 pint	6	Gray	831460	50406
		Cashmere		
1 quart	4	Gray	831461	50412
		Cashmere		
1/2 pint	6	Champagne	831462	50806
1 quart	4	Champagne	831463	50812
1/2 pint	6	Blue Moon	831464	50906
1 quart	4	Blue Moon	831465	50912
1/2 pint	6	Moroccan	831466	51706
		Red		
1 quart	4	Moroccan	831467	51712
		Red		
1/2 pint	6	Exotic	831468	51806
		Redwood		
1 quart	4	Exotic	831469	51812
		Redwood		
1 quart	4	Stain Matcher	831454	14512
		Dark Tint		
		Base		
1 gal	2	Stain Matcher	831455	14513
		Dark Tint		
		Base		

Shelf life	3 years in unopen container
Storage conditions	Store between 50° F (10°C) and 85°F (29°C). Extreme heat or freezing temperatures can damage the product, causing it to separate or thicken. Avoid freezing. Keep away from direct sunlight.
Density	7.61-8.77 lbs./US gal. (Depending on color)
Flash point	104°F (40°C)
Viscosity	30 sec ± 5 sec Ford #4 cup e 25°C
Solid content by mass	47.7% - 60.6% (Depending on color)
CSI / CSC MasterFormat®	09 93 23 INTERIOR STAINS AND FINISHES

PRODUCT DATA SHEET
 ZAR® Interior Oil Base Stain
 September 2025, Version 01.01
 020612000020223159



BUILDING TRUST



APPLICATION INFORMATION

Coverage	800 sq. ft. (74 m ²)/qt. @ 1 mil Note: Actual coverage will vary depending upon application method, surface texture, and porosity.
Drying time	<ul style="list-style-type: none">▪ 3 hrs▪ Allow non-wood surfaces to dry 48 hrs Note: Maximum cure and dry time will be prolonged when slightly humid and damp, cool conditions prevail.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

LIMITATIONS

Stains and clear finishes will not adhere to shellac or lacquer. They should be removed before refinishing.

WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop.

RAGS, STEEL WOOL, OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER USE, PLACE RAGS, STEEL WOOL, OR WASTE IN A SEALED, WATER-FILLED METAL CONTAINER.

Use only with adequate ventilation. Do not breathe vapors. Ensure fresh air entry during application and drying. If you experience eye watering, headache, or dizziness, or if air monitoring demonstrates

vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH-approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

Keep away from heat and flame. Prevent buildup of vapors by opening all windows and doors to achieve cross-ventilation.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

PRODUCT DATA SHEET
ZAR® Interior Oil Base Stain
September 2025, Version 01.01
020612000020223159



BUILDING TRUST



APPLICATION INSTRUCTIONS

BLENDING

Any two ZAR® Interior Oil Base Stain colors can be mixed together in a 50/50 blend to create unlimited color possibilities.

SUBSTRATE PREPARATION

Substrates should be clean and free from dirt, wax, and grease.

1. Fill holes and cracks with ZAR® Patch Wood Filler
2. Sand smooth with 120-150 grit sandpaper
3. Remove sanding dust and wipe clean with a tack cloth or cloth dampened with mineral spirits. Allow to dry.

Note: Oil Based Polyurethane used over light colored oil base wood stains may result in a yellow overtone if NOT exposed to natural light conditions (e.g. under rugs or low furniture).

MIXING

Stir thoroughly before and during application.

APPLICATION

APPLICATION ON BARE WOOD: Stir thoroughly before and during application. Using a lint-free cloth (like a t-shirt) or brush apply ZAR® Stain evenly in the direction of the grain and wipe off excess in the same direction. For a darker tone, re-stain when the first coat is dry. For a lighter tone, wipe the surface with a cloth dampened with mineral spirits before the stain has dried.

APPLICATION ON PAINTED AND PRE-FINISHED CABINETS: DO NOT SAND PAINTED SURFACE. Surfaces must be clean and free from dirt, wax, and grease. Painted surfaces must be thoroughly dry. Apply the stain with a clean, lint-free cloth (like a t-shirt) or brush. Apply to desired areas to achieve a glazed two-tone effect. Wipe off excess or dry brush the stain depending on

the desired look.

For pre-finished cabinets, sand the surface lightly with 320 grit sandpaper. Remove sanding dust and wipe clean with a tack cloth or cloth dampened with mineral spirits. Allow to dry. Apply stain with a clean, lint-free cloth (like a t-shirt) in the direction of the grain. Dry brush the stain to feather out corners and lap marks. Let the stain dry 48 hours and apply ZAR® Water Base or Oil Base Poly for the ultimate protection.

APPLICATION ON INTERIOR/EXTERIOR FIBERGLASS, METAL, AND COMPOSITE SURFACES: DO NOT SAND BARE EMBOSSED SURFACE.

Apply using a clean, lint-free cloth (like a t-shirt) in a circular motion (like you apply shoe polish), working the stain into the embossed grain pattern. Next, use your stain cloth to smooth the stain in the direction of the embossed grain pattern. Use a dry soft bristle brush to feather out lap marks. Allow to dry thoroughly.

Allow non-wood surfaces to dry 48 hours. For ultimate protection, top coat with ZAR® Water Base or Oil Base Poly.

APPLICATION ON GLAZING OPEN GRAINED WOODS:

This process creates a two-tone effect and is easy to do! It works best with opened grain woods such as oak.

1. Apply ZAR® Interior Oil Base Stain according to directions or leave unstained.
2. Apply one coat of ZAR® Water Base or Oil Base Poly over the stained or bare wood surface and let dry according to label instructions.
3. Apply a contrasting ZAR® Interior Oil Base Stain color wiping across the grain. Immediately wipe off the excess stain and let dry for 24-48 hours depending on temperature and humidity. For ultimate protection topcoat with ZAR® Water Base or Oil Base Poly.

PRODUCT DATA SHEET

ZAR® Interior Oil Base Stain
September 2025, Version 01.01
020612000020223159



BUILDING TRUST



CLEANING

Clean up using mineral spirits.

Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at www.zar.com or by calling SIKA's Technical Service Department at 1-800-272-3235, option 2. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's

and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/about-us/terms-conditions-of-sale.html> or by calling 1-800-272-3235, option 2.

PRODUCT DATA SHEET

ZAR® Interior Oil Base Stain
September 2025, Version 01.01
020612000020223159

