



# PRODUCT DATA SHEET

Publication Date: 3-18-21

## UGL® Pro ZAR® Interior Latex Base Trowelable Wood Patch

### PRODUCT DESCRIPTION

UGL® ZAR® Trowelable Wood Patch is a low odor, ready-to-use, full trowel latex patching compound for interior use only. Trowelable Wood Patch contains treated pulverized wood to fill nail holes, repair cracks, gouges, chips, etc., in all types of wood. Special property allows ZAR® Wood Patch to accept stain more uniformly than other wood fillers.

ZAR® Trowelable Wood Patch may be nailed, sawed, sanded, or drilled. ZAR® Wood Patch will take paint, varnish, shellac, polyurethanes and stains. When a patched area requires stain, ZAR® Wood Patch greatly diminishes the lighter area of “halo” effect surrounding the patch normally present with other wood fillers. ZAR® Wood Patch is non-flammable.

- Full trowel latex patching compound for floors
- Fills cracks, holes and gouges
- Accepts stain uniformly
- Greatly diminishes the lighter area or “halo” effect surrounding the patch when patch requires a wood stain
- May be sanded, nailed, sawed, drilled, painted, varnished, shellacked, polyurethaned or stained
- Water mixable
- Non-flammable, low odor

### BASIC USES

ZAR® Trowelable Wood Patch’s creamy easy-to-sand formula is ideal for floor finishing. It fills open-grain and nail holes and repairs cracks, gouges and minor blemishes on wood floors.

### TECHNICAL DATA

**COMPOSITION:** Latex base

**% WEIGHT SOLIDS:** 68 ± 2%

**DENSITY (LBS./US GAL.):** 13.65 ± 0.2

**VISCOSITY:** N/A

**pH:** N/A



#### COVERAGE

122 cubic inches per gallon or 600 - 850 square feet per gallon

429 cubic inches per 3.5 gal. or 2,100 - 2,975 square feet per 3.5 gallon



#### SET TIME

1 hour 30 minutes - 2 hours



#### CLEAN-UP

Remove excess with cloth dampened with water before material dries.

Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

## UGL® PRO ZAR® INTERIOR LATEX BASE TROWELABLE WOOD PATCH

### COLOR:

- Red Oak
- White Oak

### SET TIME:

- For latex stain or paint: 1½ - 2 hours
- For oil base stain, paint, varnish, shellac or polyurethane: overnight

**Note:** Maximum cure and dry time will be prolonged when slightly humid and damp, cool conditions prevail.

### COVERAGE:

- 122 cu. in./gal. or 600 - 850 sq. ft./gal.
- 429 cu. in./3.5 gal. or 2,100 - 2,975 sq. ft./3.5 gal.

Note: Actual coverage will vary depending upon depth of patch, application method, surface texture, and porosity.

**SHELF LIFE:** 3 years unopened container

**FREEZE/THAW:** Protect from freezing

**CONTAINER SIZES:** 1 gallon and 3.5 gallon containers

### VOC

White Oak does not exceed 50 g/L  
Red Oak does not exceed 100 g/L

### TINTING

All colors tintable.

### LIMITATIONS

Do not use a metal trowel or scraper. Do not use on exterior surfaces. Do not bleach.

### SURFACE PREPARATION

Remove all dirt, grease, oil and loose particles from the patch area. Dampen surfaces to be patched with water. Do not use when material and/or air temperature is below 50°F.

### APPLICATION

Pour ZAR® Trowelable Wood Patch on the floor surface. Using a non-metallic, smooth edge finishing trowel spread the wood patch across the entire surface. Be sure to press ZAR® Trowelable Wood Patch into the surface to fill all cracks. May

be sanded after one hour. Deep areas should be filled in layers allowing each layer to dry between applications. Sand after last layer has completely dried. Final sanding should remove all ZAR® Trowelable Wood Patch from the surface of the wood leaving the patch only in the surface cracks and nail holes.

Allow overnight drying of patch before applying an oil base stain - 1½ to 2 hours before applying latex paint.

### WARNING

If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### MAINTENANCE

N/A

### CAUTION

**AVOID BREATHING SANDING DUST.**

**KEEP OUT OF REACH OF CHILDREN.**

**KEEP FROM FREEZING.**

**CLOSE CONTAINER AFTER EACH USE.**

### FIRST AID

**EYES:** Immediately flush eye thoroughly with water for at least 15 minutes. Consult a physician if irritation persists.

**SKIN:** Wash affected area with soap and water. Consult a physician if irritation is present.

**INGESTION:** Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth. Place individual on the left side with head down. Contact a physician, medical facility or poison control center for advice about whether to induce vomiting.

**INHALATION:** Remove to fresh air.

## UGL® PRO ZAR® INTERIOR LATEX BASE TROWELABLE WOOD PATCH


**⚠ WARNING: Cancer and Reproductive Harm**  
– [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

For additional health and safety information,  
please refer to the Safety Data Sheet (SDS).

ZAR® is a registered trademarks of United Gilsonite Laboratories  
(UGL).

DISCLAIMER: This information is furnished without warranty,  
representation, inducement or license of any kind, except that it is  
accurate to the best of UGL's knowledge, or obtained from sources  
believed by UGL to be accurate, and UGL does not assume any  
legal responsibility for use or reliance upon same. Before using any  
product, read the label.

**Note:** Color swatches are representative only.



**Red Oak**



**White Oak**

	<b>CONTAINER</b>	<b>NUMBER/CASE</b>	<b>COLOR</b>	<b>ORDER NUMBER</b>
UGL® Pro ZAR® Interior Latex Base Trowelable Wood Patch	1 gallon	2/case	Red Oak	31113
UGL® Pro ZAR® Interior Latex Base Trowelable Wood Patch	3.5 gallon	1/case	Red Oak	31160
UGL® Pro ZAR® Interior Latex Base Trowelable Wood Patch	1 gallon	2/case	White Oak	31213
UGL® Pro ZAR® Interior Latex Base Trowelable Wood Patch	3.5 gallon	1/case	White Oak	31260



**1-800-845-5227 • Fax 1-570-969-7634 • [www.ZAR.com](http://www.ZAR.com)**

Corporate Office: 1396 Jefferson Avenue, Dunmore, PA 18509  
Mail to: P.O. Box 70, Scranton, PA 18501-0070  
Plant Locations: Jacksonville, IL • Jackson, MS