SAFETY DATA SHEET

Issuing Date 07-May-2013 Revision Date 14-Mar-2014 Revision Number 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier 311,312,313

Product Name ZAR Trowelable Wood Patch – All Colors

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Caulking

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Address

United Gilsonite Laboratories 1396 Jefferson Ave. Dunmore PA 18509 US Phone:570-344-1202 Fax:570-969-7634 Email:sales@ugl.com

Email:sales@ugl.com Contact Phone 570-344-1202

Emergency telephone number (800) 424-9300 Chemtrec

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

| Serious eye damage/eye irritation | Category 2 |
|-----------------------------------|-------------|
| Germ cell mutagenicity | Category 1B |

GHS Label elements, including precautionary statements

Emergency Overview

Hazard statements Causes serious eye irritation May cause genetic defects Appearance Multiple Colors Physical State Paste Liquid Odor Amine

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not Applicable

Unknown Toxicity

75% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Causes mild skin irritation

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS-No | Weight % | Trade Secret |
|------------------|------------|----------|--------------|
| Limestone | 1317-65-3 | 30 - 60 | * |
| Mica | 12001-26-2 | 1 - 5 | * |
| Stoddard solvent | 8052-41-3 | 1 - 5 | * |
| Raw umber | 12713-03-0 | 1 - 5 | * |
| Iron oxide | 1309-37-1 | 1 - 5 | * |

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice Show this safety data sheet to the doctor in attendance.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if applicable, and continue flushing. Keep eye wide open while

rinsing. Do not rub affected area. If symptoms persist, call a physician.

Skin Contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

physician.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Clean mouth with water and afterwards drink plenty of water.

Never give anything by mouth to an unconscious person. Consult a physician.

Protection of First-aiders Avoid contact with skin, eyes and clothing. Use personal protective equipment. For

personal protection see Section 8.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms/Effects Burning sensation.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

No information available

Uniform Fire Code Irritant: Liquid

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No

Sensitivity to Static Discharge No

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with skin, eyes and clothing. Use personal protective equipment.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up

Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled

containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes and clothing. Do not eat, drink or smoke when using this product. Remove and

wash contaminated clothing before re-use.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Incompatible ProductsNone known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|------------------|-------------------------------------|--|---|
| Limestone | - | TWA: 15 mg/m ³ | TWA: 5 mg/m ³ respirable dust |
| 1317-65-3 | | TWA: 5 mg/m ³ | TWA: 10 mg/m ³ total dust |
| | | (vacated) TWA: 15 mg/m ³ | |
| | | (vacated) TWA: 5 mg/m ³ | |
| Mica | TWA: 3 mg/m ³ | TWA: 20 mppcf (<1% crystalline | IDLH: 1500 mg/m ³ containing |
| 12001-26-2 | | silica) | <1% quartz |
| | | 3 mg/m³ (vacated) | TWA: 3 mg/m ³ respirable dust |
| Stoddard solvent | TWA: 100 ppm | TWA: 500 ppm | IDLH: 20000 mg/m ³ |
| 8052-41-3 | | TWA: 2900 mg/m ³ | Ceiling: 1800 mg/m ³ 15 min |
| | | (vacated) TWA: 100 ppm | TWA: 350 mg/m ³ |
| | | (vacated) TWA: 525 mg/m ³ | |
| Raw umber | - | (vacated) Ceiling: 5 mg/m ³ | IDLH: 500 mg/m ³ Mn |
| 12713-03-0 | | Ceiling: 5 mg/m ³ Mn | TWA: 1 mg/m ³ Mn |
| | | | STEL: 3 mg/m ³ Mn |
| Iron oxide | TWA: 5 mg/m ³ respirable | TWA: 10 mg/m ³ fume | IDLH: 2500 mg/m ³ Fe dust and |
| 1309-37-1 | fraction | (vacated) TWA: 10 mg/m ³ fume | |
| | | | TWA: 5 mg/m ³ Fe dust and fume |

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health.

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection If splashes are likely to occur, wear: Safety glasses with side-shields. None required for

consumer use.

Skin and Body Protection Wear protective gloves/clothing.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes and clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling

None known

the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

 Physical State
 Paste Liquid

 Appearance
 Multiple Colors
 Odor
 Amine

Color No information available Odor Threshold No information available

Property Values Remarks/ Method

Hq None known Melting/freezing point No data available None known 100 °C / 212 °F 5001 C / 9034 F **Boiling Point/Range** None known Flash Point None known **Evaporation rate** No data available None known Flammability (solid, gas) No data available None known

Flammability Limits in Air

Upper flammability limit
Lower flammability limit
No data available
No data available
Vapor pressure
No data available

Vapor density No data available None known **Specific Gravity** No data available None known Water Solubility Soluble (>1%) None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known **Autoignition temperature** No data available None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known None known

Dynamic viscosityNo data availableExplosive PropertiesNo data availableOxidizing PropertiesNo data available

Other Information

Softening PointNo data availableVOC Content (%)No data availableParticle SizeNo data availableParticle Size DistributionNo data available

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation May cause irritation of respiratory tract.

Expected to be an irritant based on components. May cause redness, itching, and pain.

May cause temporary eye irritation.

Skin Contact May cause irritation. Prolonged contact may cause redness and irritation.

Ingestion Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal

irritation, nausea, vomiting and diarrhea.

Component Information

| Chemical Name | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|---------------|---------------------|-------------|-----------------|
| Iron oxide | > 10000 mg/kg (Rat) | - | - |
| 1309-37-1 | | | |

Information on toxicological effects

Symptoms May cause redness and tearing of the eyes.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects There is no data available for this product Contains a known or suspected mutagen

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|---------------|-------|---------|-----|------|
| Iron oxide | | Group 3 | | |
| 1309-37-1 | | | | |

IARC: (International Agency for Research on Cancer) Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive Toxicity No information available

STOT - single exposure No information available.

STOT - repeated exposureNo information available.

Chronic Toxicity Contains a known or suspected mutagen. Possible risks of irreversible effects. May cause

adverse effects on the bone marrow and blood-forming system. Carcinogenic potential is

unknown.

Target Organ Effects Eyes. May affect the genetic material in germ cells (sperm and eggs). Blood. Central

nervous system (CNS). Kidney. Respiratory system. Skin. Liver. Testes

Aspiration Hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

Not applicable

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40)

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional,

or local regulations for additional requirements.

Contaminated Packaging Dispose of in accordance with local regulations.

California Hazardous Waste Codes 331

14. TRANSPORT INFORMATION

DOT NOT REGULATED

Proper Shipping Name Non regulated

Hazard Class N/A

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA Not regulated Proper Shipping Name Non regulated

Hazard Class N/A

IMDG/IMO Not regulated

Hazard Class N/A

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

SARA 311/312 Hazard Categories

Acute Health HazardYesChronic Health HazardYesFire HazardNoSudden Release of Pressure HazardNoReactive HazardNo

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania | Rhode Island | Illinois |
|-------------------------------|------------|---------------|--------------|--------------|----------|
| Limestone 1317-65-3 | Х | X | Х | | |
| Mica 12001-26-2 | Х | Х | Х | | |
| Iron oxide 1309-37-1 | Х | Х | Х | | |
| Stoddard solvent 8052-41-3 | Х | Х | Х | | |

International Regulations

Mexico

National occupational exposure limits

| Component | Carcinogen Status | Exposure Limits |
|-----------------------|-------------------|------------------------------------|
| Limestone | | Mexico: TWA= 10 mg/m ³ |
| 1317-65-3 (30 - 60) | | Mexico: STEL= 20 mg/m ³ |
| Mica | | Mexico: TWA= 3 mg/m ³ |
| 12001-26-2 (1 - 5) | | _ |

| Stoddard solvent | Mexico: TWA 100 ppm |
|---------------------|-------------------------------------|
| 8052-41-3 (1 - 5) | Mexico: TWA 523 mg/m ³ |
| | Mexico: STEL 200 ppm |
| | Mexico: STEL 1050 mg/m ³ |
| Iron oxide | Mexico: TWA 5 mg/m ³ |
| 1309-37-1 (1 - 5) | Mexico: STEL 10 mg/m ³ |

Mexico - Occupational Exposure Limits - Carcinogens

Canada WHMIS Hazard Class D2A Very toxic materials



16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 0 Instability 0 Physical and Chemical Hazards -

HMIS Health Hazard 2* Flammability 0 Physical Hazard 0 Personal Protection X

Chronic Hazard Star Legend *Indicates a chronic health hazard.

Prepared By EHS Department

Issuing Date 07-May-2013

Revision Date 14-Mar-2014

Revision Note No information available

General Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet